

VANTAGE®
HELMET MOUNTED TACTICAL LIGHT

MARKET
APPLICATIONS: Fire & Rescue, Industrial

DESCRIPTION:

Lightweight, compact and low profile, the VANTAGE® has been designed to easily attach above or below full brim Fire and Industrial helmets. The light features the latest in power LED technology combined with an ultra-bright blue LED safety tail light. Powered by lithium batteries, the C4®LED technology produces 2 to 3 times the output of previous LEDs. Sealed for water-resistance.

CASE MATERIAL:

 6000 series machined aircraft aluminum with black anodized finish.
 High impact, chemically resistant engineering polymer LED housing.

DIMENSIONS:

 Length: 3.26 in. (8.28 cm) Width: 1.47 in. (3.73 cm) Height with clamp: 2.56 in. (6.50 cm)
 Height above/below mounting surface: 1.84 in. (4.67 cm)

WEIGHT:

5.14 oz (145.7 grams) with batteries (included in purchase).

LENS:

High temperature, shock mounted, impact resistant Boro Float glass.

LIGHT SOURCE:

 C4®LED technology, impervious to shock with a 50,000 hour lifetime.
 470nm Ultra-bright blue LED safety tail light with a 100,000 hour lifetime.

LIGHT OUTPUT:

7,000 candela peak beam intensity, 167m beam distance and 115 lumens measured system output.



Textured parabolic reflector produces a smooth beam hotspot with optimum peripheral illumination to aid in navigation. Optimized electronics provides regulated intensity.

ON/OFF:

Dual direction, easy access On-Off switch located on rear of light.

RUN TIME:


6 continuous hours to 10% of initial lumen output.

BATTERY:

Two (2) 3 Volt CR123A lithium batteries, with a storage life of 10 years.

FEATURES:

 C4®LED technology for extreme brightness.
 IPX7 rated design; waterproof to 1 meter for 30 minutes.
 Swivel clamp and insertable 5° angle adjuster to optimize beam location.
 Ultra-bright blue LED safety tail light visible in heavy smoke.
 Serialized for positive identification.

WARRANTY:

Streamlight's Limited Lifetime Warranty.

APPROVALS:

 Meets applicable European Community Directives. 
 Meets requirements of NFPA 1971-8.6 (2007)

OPTIONAL
ACCESSORIES: N/A
