



- NOTES:**
1. INLET: 5/16" BARB
 2. OUTLETS: 5/16" BARB W/ SHUTOFF
 3. GAUGES: 60# (3 EA)
 4. SAFETY BLOW-OFF: 60 ± 5 PSI
 5. WORKING PRESSURE: 0-50 PSI
 6. POLY BONNETS WITH ADJ GOLD CAPS

| | | |
|-----------------------------|---|--------------|
| MATERIAL | NAME | DATE |
| FINISH | DRAWN | JRS 09/16/11 |
| DIMENSIONS ARE IN INCHES | ENG APPR. | PF |
| TOLERANCES: | PROPRIETARY AND CONFIDENTIAL | |
| FRACTIONAL ± 1/64 | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASCO MFG., INC. IS PROHIBITED. | |
| ANGULAR: MACH ± 1/2° | | |
| BEND ± | | |
| TWO PLACE DECIMAL ± 0.015 | | |
| THREE PLACE DECIMAL ± 0.005 | | |

TAPRITE
 248 NORTHWESTERN DR SAN ANTONIO TX 78228

TITLE: **REG BEER PNL, 3P3P, 3Y, JUMPR, 60" 5/16B IN/SHTFF, CO2 TBG, 16" X 8.5"**

| | |
|------------------------------|----------|
| SIZE DWG. NO. | REV |
| B T1683STWMK-01_SALES | C |

SCALE: 2:3 DO NOT SCALE DRAWING SHEET 1 OF 1