



844-pik-fast • www.pik-fast.com

# PRODUCT DATA SHEET

## FM1104ATG - Super Sticky High Tack ATG

### Description:

Using this high tack ATG tape offers the ability to mount to irregular, printed surfaces, and it contains the thickness in the adhesive to mount fabrics. It allows for permanent mounting and it bonds on contact and works on many different substrates.

### Features:

- No carrier film for maximum flexibility
- Extra thick adhesive for textured and irregular surfaces
- Permanently bonds papers, plastics, and films
- Useful as a core start up tape
- Acid free for archival use



Product Data				
Carrier	None	-	-	
Adhesive	Acrylic	5.0 mil	0.13 mm	
Liner	Yellow glassine paper	3.0 mil	0.08 mm	
Total Tape Thickness	Including liner	5.0 mil	0.13 mm	
Peel Adhesion	From Stainless Steel	120 oz/in	34 N/25 mm	
Temperature Resistance	-	250°F	121°C	
Recommended Industry	Framing	Awards	Signs	Trophies

### Application Notes:

Most commonly used in framing and mounting applications for setting mats and securing pictures in frames. Also very useful in automated applications like core start-up and assembly of point-of-purchase (P.O.P.) displays.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

4221 Courtney Road • Franksville, WI 53126

www.pik-fast.com • 1-844-pik-fast