



OPTIONAL
CHAMFER PER
ASME B18.9

3/8 - 16 UNRC-2A

- NOTE 1: UNDER SQUARE NECK CHAMFER IS 45 DEG MAX
 NOTE 2: FOR DIMENSIONS AND TOLERANCES NOT SPECIFIED, REFER TO ASME B18.9.
 NOTE 3: TOLERANCE ON LENGTH: +/- 0.03"
 NOTE 4: HEAD MARKING: 'TLC 5' IN THE CENTER, MANUFACTURER MARK BELOW THE TLC 5, AND STANDARD SAE J429 GR 5 RADIAL LINES AROUND THE 'TLC 5' AND MANUFACTURER MARK.

Signed: *OK. [Signature]*
6-4-13

REVISIONS				TOLERANCE/IND STD: SEE NOTE 2	MATERIAL: SAE GR 5 J429	FINISH: ZN CCR PER MAT0310	
REV	DESCRIPTION	DATE	DRAWN BY				
A	RELEASED TO PRODUCTION	6/3/13	MDB	 3216 EAST 35TH STR CT DAVENPORT, IA 52807-2501	DESCRIPTION: 3/8 - 16 UNRC-2A CONTOUR HEAD PLOW BOLTS		
					UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES		
					SHEET: 1 OF 2	SCALE: 3 : 2	TLC NUMBER: 20130603

PART	SIZE			
	DIAMETER	TPI	L	MIN THREAD LENGTH
2009351	0.375	16	1 1/2"	1.000
2024471	0.375	16	1 5/8"	1.000
2024473	0.375	16	1 3/4"	1.000

REVISIONS				TOLERANCE/IND STD: SEE NOTE 2	MATERIAL: SAE GR 5 J429	FINISH: ZN CCR PER MAT0310	
REV	DESCRIPTION	DATE	DRAWN BY				
A	RELEASED TO PRODUCTION	6/3/13	MDB	 TRINITY SUPPLY CHAIN SOLUTIONS 3216 EAST 35TH STR CT DAVENPORT, IA 52807-2501	DESCRIPTION: 3/8 - 16 UNRC-2A CONTOUR HEAD PLOW BOLTS		
					UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES		
					SHEET: 2 OF 2	SCALE: 3 : 2	TLC NUMBER: 20130603