Manufacturer PDF Provided by www.southeasternequipment.net

T290
Walk-Behind Scrubber



Simple Use for Congested Spaces
Its easy-to-maneuver design, intuitive controls and robust components provide for simple operation and maintenance. The T290 is ideal for cleaning small, congested areas found in retail stores and schools.



A Reliable Clean
Robust construction in a compact scrubber with easy-to-use pad assist or self-propel configuration.



Convenient Features
Avoid kneeling to put the brush on, with hands-free brush replacement with spin-on, spin-off feature.



Easy Daily Maintenance
Yellow touch points help reduce breakdowns by simplifying preventative maintenance.

Inside the **T290**

1. **Intuitive control panel** with an indicator light when solution tank level is low.
2. **Easy access** to internal components with tank that tilts back.
3. **Easy-to-inspect** in-line solution filter.
4. **Consistent water pick-up** with durable "V" shaped squeegee design and standard Linatex® squeegee blades.
5. **Optimum cleaning performance,** with self-leveling brush/pad.



T290 Specifications

	SPECIFICATION	
FEATURE	**PAD ASSIST**	**SELF-PROPEL**
Cleaning path	500 mm	
Productivity (per hour) theoretical max	1,820 m²/hr	
Estimated coverage (per hour)*	1,122 m²/hr	
Scrubbing speed	3.5 kmh	3.5 kmh
Scrub head raise/lower	manual with foot pedal	
Brush/pad speed	155 rpm	
Brush/pad pressure	18 kg	
Solution tank capacity	40 L	
Recovery tank capacity	50 L	
Battery run time - up-to hours (150AH Gel Battery)**	3.0	2.6
Battery voltage	24V (2x12)	
Dimensions (L x W x H)	1,230 x 516 x 960 mm	
Squeegee width	815 mm	
Weight (with heaviest battery)	157 kg	162 kg
Sound level (operator's ear)***	74 dB	

Specifications subject to change without notice.
** Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.*
*** Run times are based on Continuous Scrubbing Run Times.*
**** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA*

For a demonstration or additional information,
call **+1.800.553.8033** or email **info@tennantco.com**

t290-brochure-en-au 7/22 *©2022 The Tennant Company.*

Tennant Australia
Unit 11, 4 Southridge Street
Eastern Creek NSW 2766
T: 1800 226 843 (FREE CALL)
T: +61 2 9839 9700
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand
Unit 5, 103 Cryers Road
East Tamaki
Auckland 2013
T: +64 9 253 9013
F: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com