

FLORIM BASALTINE

GLAZED PORCELAIN



tierra sol



Nominal Sizes



12x24 - Rectified



Special order: 24x48, 24x24, 18x36,
6x24, 12x12, 12x12 Grip finish

Colors




White



Sand



Light Grey



Dark Grey

Special order: Nut

Decors and Special Pieces

2x2 Mosaic



12x12 Sheet



3x12 Bullnose

Special Order:
6x12 Cover Base

Recommended applications

Residential	Bath / Shower
Light commercial	Indoor
Medium commercial	Wall
Fireplace	Floor

Characteristics of tile

Low maintenance	Fade resistant
Stain resistant	Hypoallergenic
Resistant to fungus	Odour resistant

Technical specifications

CGSB Type	7	MOHS	≥ 7
PEI	4	Tile thickness	10 mm
Dynamic Coefficient of Friction	≥ 0.42	Chemical Resistance	Not Affected
Friction Coefficient	n/a	Variation	V1 V2 V3 V4 Moderate
Frost Resistance	Yes		
Water Absorption	≤ 0.5%		

Special instructions

- Shade variations between tiles is characteristic. Color may vary from sample.
- For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.



www.TierraSol.ca