844-pik-fast • www.pik-fast.com

PRODUCT DATA SHEET

FM2000 - Framer's Tape II

Description:

Our tape is stronger and thinner than linen or paper tapes. It is moisture proof and the adhesive will not ooze from the sides. This product is great with water colors and can be repositioned on hard calendared mat board surfaces. This flexible adhesive comes in white or clear and can be easily reversed with minimal heat from most surfaces.

Features:

- Flexible backing
- Stronger than paper
- Removable with heat
- Archival Grade
- pH Neutral
- Available in white or clear

G	FM2000-.75WH	3/4" x 180FT
G	FM2000-1WH	1" x 180FT

Product Data				
Backing	Polyproylene Film	2.0 mil	0.051 mm	
Adhesive	Emulsion Acrylic	1.0 mil	.025 mm	
Liner	None	-	-	
Total Tape Thickness		3.0 mil	0.076 mm	
Peel Adhesion	From Stainless Steel	22 oz/in	6.12 N/25 mm	
Tensile Strength		32 lbs/in	142 N/25 mm	
Temperature Range		32°F-150°F	0°C- 49°C	
Recommended Industry	Framing	Awards	Signs	Trophies

Application Notes:

Heavy hinging, mending, sealing, mounting, repairing and reinforcing applications are most common for this product.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity

4220 Courtney Road • Franksville, WI 53126
www.pik-fast.com • 1-844-pik-fast