

Convenient pressure testing with an easy-to read display, built-in magnet and intuitive interface



Functions

- Range of -60 to +60 inH2O
- Differential Pressure

Features

- Dual input differential measurement up to 80.27 inches of water column within range
- Measures in 11 scales; inH2O, psi, bar, mBar, kPa, inHG, mmHG, ozin, FtH2O, cmH2O and kgcm.
- Magnetic mount
- Auto ranging
- Backlit display
- Data hold
- Max/Min
- Zero button
- 1-Year limited warranty

Applications

- Validate pressures in accordance with equipment manufacturer's specification for optimal system efficiency and safety.
- Measure draft, gas supply, manifold or burner pressures
- Dual input offers users the ability to measure pressure drops across heat exchangers, cooling coils, supply and return registers and filters





Includes

- Flexible transparent silicone tubing (2) 18" length 1/4" diameter
- Barbed gas valve fitting (2)
- Soft pouch (7.48" x 4.33" x 1.96")
- Manual
- Battery

Specifications

| Unit of Measure | Range | Resolution | Accuracy (77°F) |
|-----------------|---------|------------|--------------------------|
| bar | ± 0.200 | 0.001 | ± 0.3% Full Scale Output |
| Ounces/Sq. Inch | ± 46.60 | 0.01 | |
| psi | ± 2.900 | 0.001 | |
| inHg | ± 5.904 | 0.001 | |
| mBar | ± 200.0 | 0.1 | |
| mmHg | ± 150.0 | 0.1 | |
| kPa | ± 20.00 | 0.01 | |
| Kg/Sq. cm | ± 0.204 | 0.001 | |
| InH2O | ± 60 | 0.01 | |
| FtH2O | ± 6.689 | 0.001 | |
| cmH2O | ± 203.9 | 0.1 | |

Downloads



Manual



Data Sheet



Made in CHINA