

FROSTED POST TOP RETROFITS 360° OMNI DIRECTIONAL DESIGN



 120-277V	 E26/EX39	 ULTYPE B BALLAST BYPASS	 -40°F TO 122°F	 ACTIVE COOLING	 6kA	 80+	 L70 50,000	 5 YEAR WARRANTY
VOLTAGE	MEDIUM + MOGUL BASES	INSTALL METHOD	OPERATING TEMP	ACTIVE COOLING	SURGE PROTECTION	CRI	RATED LIFE	WARRANTY

softer ambience



LED-8046M

runs cooler so it lasts longer

- Available in 45W & 65W models replacing up to 320W HID.
- Advanced active cooling. Energetic cooling fan & dynamic temp control supports a longer, brighter life.
- Multi-directional mounting capability & 360° design. Use base down, base up or base sideways without affecting performance.
- Pretested & potted drivers are burnt in 3x prior to shipping and protected against vibration & moisture.
- Expertly engineered to work efficiently in enclosed fixtures & damp environments, while also protected against insects & dust.
- Dual stage MOV protection with integrated 6kA surge.
- USA designed & specified LED driver.

PART #	UPC	REPLACES	WATTAGE	LUMENS	CCT (K)	BASE
LED-8024E40-FR	844006023836	250W	45W	5950	4000K	E26
LED-8046M40-FR	844006023843	320W	65W	8550	4000K	EX39



FOR PRODUCT INFO ("LED" MODEL #) CONTACT.....Light Efficient Design • 188 S. Northwest Highway • Cary, IL 60013 • 847.380.3540 • led-llc.com
 FOR PRODUCT INFO ("RP" MODEL #) CONTACT.....RemPhos by Light Efficient Design • 30 Log Bridge Road, Building 200 • Middleton, MA 01949 • 877.997.3674 • remphos.com