

X1S2650



16GA Wide Crown Stapler

Applications

Lathing, Wall Panel Construction



Specifications

Fastener Crown	15/16"
Fastener Length	1" - 2"
Magazine Capacity	150
Actuation Mode	Selective Actuation
Dimensions	14" x 3-1/2" x 9-3/4"
Weight	4.8 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.042 SCF
Noise Power Emissions per EN12549 LwA,1s	106.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	105.0 dBA
Vibration Emissions per ISO-8662-11	3.39 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Aluminum Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessories

Air Filter (P-97454), Full Sequential Actuation Trigger (AS-21037), Lathing Safety Adaptor (AS-53085), Walking Stick Attachment (AS-99105)

For Best Results, Use Spotnails® Collated Fasteners

16GA 15/16" Wide Crown Staples

(Similar to Paslode® GSW16)

Stock No.	LENGTH
Galvanized	
2608PG-10M	1"
2610PG-10M	1-1/4"
2612PG-10M	1-1/2"
2614PG-10M	1-3/4"
2616PG-10M	2"
304 Stainless Steel	
2608PS-10M	1"

RELIABILITY
Provin

Jan. 2022

Division of Peace Industries, LTD.

P: 800-873-2239 / 847-259-1620 | F: 888-369-2588 | customerservice@spotnails.com
SPOTNAILS.BIZ | SPOTNAILS.COM | RELIABILITYPROVIN.COM