



**NOTES:**

1. INLET: CO2 FITTING W/ CGA 320 NUT
2. OUTLETS: 1/4" BARB WITH BALL-CHECK
3. GAUGES: 160# & 2000#
4. SAFETY BLOW OFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, RED

MATERIAL	DRAWN	NAME	DATE
		LG	08/12/13
FINISH	ENG APPR.		
<b>PROPRIETARY AND CONFIDENTIAL</b>			
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.			
DIMENSIONS ARE IN INCHES			
TOLERANCES:			
FRACTIONAL ± 1/64			
ANGULAR: MACH ± 1/2°			
BEND ±			
TWO PLACE DECIMAL ± 0.015			
THREE PLACE DECIMAL ± 0.005			



3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238

TITLE: **REG PRI SODA, 2P2P, 160#, TNK FTG 1/4B-CV, 2000#, POLY RED**

SIZE	DWG. NO.	REV
<b>A</b>	T5752HP-01_SALES	-

SCALE: 1:1	DO NOT SCALE DRAWING	<b>SHEET 1 OF 1</b>
------------	----------------------	---------------------