

W1S4840



18GA Narrow Crown Stapler

Applications

Cabinet Assembly, Door & Window Manufacturing,
Drawer Assembly, Floor Underlayment, Furniture Assembly



Specifications

Fastener Crown	1/4"
Fastener Length	3/8" - 1-5/8"
Magazine Capacity	168
Actuation Mode	Selective Actuation
Dimensions	12" x 2-1/2" x 9-1/2"
Weight	3.9 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.035 SCF
Noise Power Emissions per EN12549 LwA,1s	108.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	106.1 dBA
Vibration Emissions per ISO-8662-11	3.48 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control,
Ergonomic Rubber Grip, Quick Clear Nose,
Top Load Steel Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessories

Driver Blade 110.3mm (P-06302), Full Sequential
Actuation Trigger (AS-21040), Long Magazine
Available (W1S4840LM), No Mar Safety Kit
(AS-53068), Positive Placement Assembly
Adaptor (AS-99080)

For Best Results, Use Spotnails® Collated Fasteners

18GA 1/4" Narrow Crown Staples

(Similar to Senco® L / Duo-Fast® 1800)

Stock No.	LENGTH	M/ Bx	Bx/ Cs	Stock No.	LENGTH	M/ Bx	Bx/ Cs
PG - Made of High Tensile Wire				Divergent Galvanized			
4803PG-50M	3/8"	5	10	4807DG-50M	7/8"	5	10
4804PG-50M	1/2"	5	10	4809DG-30M	1-1/8"	5	6
4804.5PG-50M	9/16"	5	10	Outward Clinch Galvanized			
4805.5PG-50M	11/16"	5	10	4805OCG-50M	5/8"	5	10
4805PG-50M	5/8"	5	10	Nylon			
4806PG-50M	3/4"	5	10	4811PN-30M	1-3/8"	5	6
4807PG-50M	7/8"	5	10	304 Stainless Steel			
4808PG-50M	1"	5	10	4803PS-50M	3/8"	5	10
4809PG-30M	1-1/8"	5	6	4805PS-25M	5/8"	2.5	10
4810PG-30M	1-1/4"	5	6	4806PS-25M	3/4"	2.5	10
4811PG-30M	1-3/8"	5	6	4807PS-25M	7/8"	2.5	10
4812PG-30M	1-1/2"	5	6	4808PS-25M	1"	2.5	10
4813PG-30M	1-5/8"	5	6	4810PS-25M	1-1/4"	2.5	10
Cross Chisel Galvanized				4812PS-25M	1-1/2"	2.5	10
4805CG-50M	5/8"	5	10				
4806CG-50M	3/4"	5	10				



Jan. 2022