



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 200°F with LED rocker switch and hour/tach meter

American made
heavy duty 7000 PSI rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD steel tube frame**, with centre balanced lift hook (above industry standards)

Powerase electric start w/ 18amp charge

Triplex direct-drive AR pump carries a **5-year warranty**

Adjustable pressure relief valve

12" oil drain hose for ease of maintenance

7-gallon, removable, rust-proof polyethylene fuel tank with fuel gauge in cap

Brake kit assembly

Marine sealed battery box with 55 AH AGM deep cycle battery

3/4" HD Threaded mount axle

360° Hose reel swivel bracket (sold separately: 59.400.001)



POWER EASE

HEATING COIL
1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5500PSI Rated, "Full Sized" 96' length for maximum heat rise and proper heat production

Stainless-steel coil skin provides extra durability and resists corrosion

12v DC Oil-fired Beckett burner with low voltage inhibitor, prevents burner from starting up if battery voltage is dropped

Mounting bracket for truck mounting

12" heavy-duty flat free tires

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50' high pressure hose w/quick connects
- 20% chemical injector assembly with quick connects
- 4 color-coded QC spray nozzles
- 1 color-coded QC chemical nozzle



DIRECT DRIVE

MODEL	GPM	PSI	ENGINE	BURNER	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW4015RA	4	4000	POWERASE	12v-oil	330,000	AR RSV4040	DIRECT	2.21 GPH	47"L x 31"W x 50"H	52"L x 36"W x 55"H	530