

PT-CN55



Coil Siding and Fencing Nailer

Applications

Fencing, Siding



Specifications

Diameter	.083 - .092
Fastener Length	1" - 2-1/4"
Magazine Capacity	300
Actuation Mode	Contact Actuation
Dimensions	12" x 5" x 12"
Weight	5.95 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.053 SCF
Noise Power Emissions per EN12549 LwA,1s	110.1 dBA
Noise Pressure Emissions per EN12549 LpA,1s	100.5 dBA
Vibration Value per ISO-8662-11	12.49 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Body Protector, Ergonomic Rubber Grip, Narrow Nose for Accurate Nail Placement, Protective Dust Cover, Side Load Nylon Magazine

Includes

Air Fitting, Allen Wrenches, Safety Glasses, Tool Oil

Accessory

Remote Valve (RE-MXRCV70)

For Best Results Use Spotnails® Collated Fasteners

15° Wire Weld Siding and Fencing Flat Coil Nails

Stock Number	Size	Description	Stock Number	Size
.083 Flat Coil			.090 - 304 Stainless Steel	
CW3D083R	1-1/4"	Ring, Bright	CW4D090SSR-3.6M	1-1/2"
CW3D083RG	1-1/4"	Ring, Galv	CW5D090SSR-3.6M	1-3/4"
CW4D083R	1-1/2"	Ring, Bright	CW5.5D090SSR-3.6M	1-7/8"
CW4D083RG	1-1/2"	Ring, Galv	CW6D090SSR-3.6M	2"
CW5D083R	1-3/4"	Ring, Bright	CW7D090SSR-3.6M	2-1/4"
CW5D083RG	1-3/4"	Ring, Galv	.092 Flat - Hot Dipped Galvanized	
CW5D083S	1-3/4"	Screw	CW3D092RHDG	1-1/4"
CW6D083R	2"	Ring, Bright	CW4D092RHDG	1-1/2"
CW6D083RG	2"	Ring, Galv	CW5D092RHDG	1-3/4"
.090 Flat Coil			CW6D092RHDG	2"
CW7D090RG-4.2M	2-1/4"	Ring, Galv	CW7D092RHDG	2-1/4"