	Project N Model #:	Name: Location:	AIA#:
	SIS#:		
Calobe		Induction Range	<b>;</b>

Model

IR1800 - 1800W Countertop Induction Range

Ideal for buffet and omelet stations, catering operations, cafeterias, and more...

For noncontinuous use









Most energy efficient cooking in the world!

No open flames

Portable and light weight

Stores away easily

Ferromagnetic Cookware Required

## **Quality Construction**

IR1800

- Durable ceramic cooktop with stainless steel framing
- Low profile, 2.75" H
- Easy-to-clean flat surface control panel
- · Durable molded plastic bottom

### **Applications**

 sautéing, warming, and cooking, sauces, butter, chocolate, eggs, soups, etc.

## Warranty

One-year parts and labor

### **Standard Features**

- 1800W, 120V
- 6 power levels
- Touch pad controls and 4 digit LED display
- · Digital timer with repeat time selection
- Proper pan detection and automatic empty pan safety shut-off
- 6 temperature settings from 150°F-450°F
- Error code alert display
- Attached 5½-foot power cord and NEMA 5-15P plug

# **Optional:**

• 5-20P plug (Canada)
Canada NEMA and ETL listed units available.
Please specify when ordering.



Approved by:	Date:	



#### **SPECIFICATIONS**

- · Durable ceramic cooktop with stainless steel framing
- · Touch pad controls and 4 digit LED display
- · Proper pan detection and automatic empty pan safety shut-off
- 6 Temperature settings from 150°F-450°F
- · Error code alert display
- · Adjustable foot for leveling unit
- Attached 5½-foot power cord and plug

Model	Power Levels	Temp Settings	Cooking Surface	Electric	AMPs	Wattage	NEMA Plug Type
IR1800	6	150°F-450°F	4.75" to 9.5"	120V/60Hz	15	1800 W	5-15P (U.S.) 😲
							5-20P (Canada)

#### **IMPORTANT: PERSONS WITH PACEMAKERS**

Persons with pacemakers should stay at least 3 feet away from the induction range. When using the induction range with the general public, a pacemaker notice should be posted near the induction range.

#### **STANDARD FEATURES:**

Auto pan detection: Range detects if proper cookware/pan is placed on cooktop.

Automatic shut-off: Automatically shuts off when timer runs to "0".

Over-heat protection: If pan overheats and/or the electrical components overheat, the unit shuts off.

Digital timer: Set timer from 0-170 minutes.

Bright LED display: Bright 4 digit LED display for easy viewing.

#### **Suitable Pans:**

Steel or cast iron, enameled cast iron, stainless steel and aluminum if marked "suitable for induction cooking", flat-bottom pans/pots with diameter of 12 to 26 cm or 4.75" to 10".

### **DIMENSIONS & SHIPPING INFORMATION**

Carton reinforced for shipping. The weight and dimensions of reinforced carton are listed below and may vary from shipment to shipment.

Model	Foot Print	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight
IR1800	11" W × 12.75" L	14" L × 12.06" W × 2.75" H	7.2 lbs.	17.75" L × 14.63" W× 4.875" H	8.5 lbs.
	(30 cm × 32.38 cm)	(35.7 cm × 30.6 cm × 6.9 cm)	(3.27 kg)	(45 cm × 37 cm × 12.38 cm)	(3.85 kg)