

CASALGRANDE CITTA

NON-RECTIFIED UNGLAZED PORCELAIN

tierra sol

Casalgrande Citta consists of an expressive colour palette that brings the best out of a collection of tiles renowned for their practicality, aesthetics, and strength.



Nominal Sizes and Colours










	12x24 - Lisboa
	12x24 - Praga
	12x24 - Mosca
	12x24 - Stoccolma
	12x24 - Berlino
	12x24 - Atene
	12x24 - Londra
	12x24 - Rotterdam









Special Order by Full Boxes

18x18, 12x24 Non-Rectified, 24x24, 3.5x24 Bullnose, 12x24 Gradino Step Tread















Recommended applications

 Residential	 Bath / Shower
 Light commercial	 Fireplace
 Medium commercial	 Indoor
 Wall	 Outdoor
 Floor	

Characteristics of tile

 Low maintenance	 Fade resistant
 Stain resistant	 Resistant to fungus
 Hypoallergenic	 Eco-friendly

Technical specifications

 CGSB Type	7	 MOHS	n/a
 PEI	n/a	 Tile thickness	8 mm
 Dynamic Coefficient of Friction	0.54	 Chemical Resistance	GA
 Friction Coefficient	n/a	 Variation	 V1  V2  V3  V4 Moderate
 Frost Resistance	Yes		
 Water Absorption	< 0.1%		



Special instructions

- Shade variations between tiles is characteristic. Colour may vary from sample.
- For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.



www.TierraSol.ca