



Commonly used to indicate a trouble condition in an FACP, this audible unit is compatible with our full line of Infinity modules to build a custom annunciation solution that fits your every need.

SPECIFICATIONS

Single gang IAM unit sends an audible tone out when alarm, trouble, and/or supervisory condition occurs in FACP. An input sounds the horn and lights a yellow LED, and can be silenced via the keyed or rocker switch. When the input is removed, the horn will ring back indicating that the switch needs to be normalized. Standard clinch type terminal strip used for field wiring. Accepts dry contacts and current limited inputs.

RANGE RATING

37mA @18V | 89.3mA @32V

SWITCH POWER RATINGS

3A @24VDC & VAC (Rocker) | 3A @24VDC & VAC (Keyed)

AGENCY APPROVALS

- UOXX.S2580 UL Listed Control Unit Accessories
- 7120-0553:0105 California State Fire Marshal (CSFM)

ORDERING INFORMATION

Part #	Description
IAMAUDK (SSU02500)	Audible Annunciator (Keyed)
IAMAUDR (SSU02501)	Audible Annunciator (Rocker)



FEATURES

- Scratch-resistant Lexan® face panel with a black background and white screened legend
- Durable steel frame mounts into an Infinity Gang Box or standard electrical back box and securely holds the Infinity Gang Plate
- Standard mounting hardware included
- Field selectable between 12/24 VDC

