

T1S3832



18GA Narrow Crown Stapler

Applications

Cabinet Assembly, Door & Window Manufacturing, Drawer Assembly, Floor Underlayment, Furniture Assembly, Underlayment



Specifications

Fastener Crown	3/16"
Fastener Length	1/2" - 1-1/4"
Magazine Capacity	168
Actuation Mode	Selective Actuation
Dimensions	11-1/2" x 2-1/2" x 8"
Weight	2.65 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.016 SCF
Noise Power Emissions per EN12549 LwA,1s	96.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	86.9 dBA
Vibration Value	Less than 2.5 m/s ² per ISO-8662-11
Vibration Value Uncertainty per ISO-8662-11	0.73 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Steel Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessories

Full Sequential Actuation Trigger (AS-21040), No Mar Safety Kit (AS-53100)

For Best Results, Use Spotnails® Collated Fasteners

18GA 3/16" Narrow Crown Staples

Stock No.	LENGTH	M/Bx	Bx/Cs
Galvanized			
3804PG	1/2"	5	10
3805PG	5/8"	5	10
3806PG	3/4"	5	10
3807PG	7/8"	5	10
3808PG	1"	5	10
3809PG	1-1/8"	5	10
3810PG	1-1/4"	2	10
Divergent Galvanized			
3807DG	7/8"	5	10