



844-pik-fast • www.pik-fast.com

PRODUCT DATA SHEET

FM992ATG - ULTI-MATT PREMIUM ATG TAPE

Description:

Use this great general purpose adhesive transfer tape for double matting and mounting and also ideal for sealing dust covers. The adhesive will not dry out or deteriorate with age and it is quick and easy to use. You can use this solvent resistant tape on an assortment of material groupings.

Features:

- Permanently bonds papers, plastics, and films
- Useful as a core start up tape
- Acid free for archival use

- Ⓜ FM992ATG-36 1/2" x 36YD
- Ⓜ FM992ATG-.5 1/2" x 60YD



Product Data			
Carrier	None	-	-
Adhesive (each side)	Acrylic	1.5 mil	0.038 mm
Liner	Yellow glassine paper	3.0 mil	0.076 mm
Total Tape Thickness	-	4.5 mil	0.114 mm
Tack	PSTC- 6	≤ 1 inch	
Peel Adhesion	From Stainless Steel	54 oz/in	60 N/100 mm
Temperature Resistance	-	250°F	121°C
Recommended Industry	Framing	Awards	Signs
			Trophies

Application Notes:

Most commonly used in framing and mounting applications for setting mats and securing pictures in frames. Also very useful in automated applications like core start-up and assembly of point-of-purchase (P.O.P.) displays.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity