

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: DEM01003

Product Name: Demand Products Foam Lok Adhesive 14oz

Revision Date: Jun 17, 2026 **Date Printed:** Jun 17, 2026

Version: 2.0 **Supersedes Date:** Apr 30, 2024

Manufacturer's Name: Cycan Industries, Inc.

Address: 313 Bell Park Drive Woodstock, GA, US, 30188

Emergency Phone: CHEMTREC (800) 424-9300

Information Phone Number: (877) 320-4747

Fax:

Product/Recommended Uses:

SECTION 2) HAZARDS IDENTIFICATION

Classification

Aerosols - Category 1

Acute toxicity Oral - Category 5

Aspiration Hazard - Category 1

Eye Irritation - Category 2A

Reproductive Toxicity - Category 2

Skin Irritation - Category 2

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H222 - Extremely flammable aerosol

H229 - Pressurized container; may burst if heated

Hazardous Statements - Health

H303 - May be harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation

H361 - Suspected of damaging fertility or the unborn child

H315 - Causes skin irritation

H373 - May cause damage to organs through prolonged or repeated exposure.

H336 - May cause drowsiness or dizziness

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves, protective clothing, eye protection/face protection.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P271 - Use only outdoors or in a well-ventilated area.

P233 - Keep container tightly closed.

Precautionary Statements - Response

P312 - Call a POISON CENTER/doctor if you feel unwell.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P321 - For specific treatment see section 4 of SDS.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P314 - Get Medical advice/attention if you feel unwell.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/regional/national/international regulation. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0000110-54-3	HEXANE	10.0000% - 30.0000%
0000115-10-6	METHYL ETHER	10.0000% - 30.0000%

CAS	Chemical Name	% By Weight
0000075-37-6	DIFLUOROETHANE	10.0000% - 30.0000%
0220543-67-9	Cyclopentene, polymer with 1-butene, (2E)-2-butene, (2Z)-2-butene, 2-methyl-1-propene and 1,3-pentadiene	7.0000% - 13.0000%
0000110-82-7	CYCLOHEXANE	5.0000% - 10.0000%
0025038-32-8	Isoprene-Styrene Polymer	5.0000% - 10.0000%
0000079-20-9	METHYL ACETATE	1.0000% - 5.0000%
0003710-84-7	DIETHYL HYDROXYLAMINE	0.1000% - 1.0000%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Indication of any immediate medical attention and special treatment needed

Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

Most important symptoms and effects, both acute and delayed

No data available.

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Eliminate all ignition sources if safe to do so. Get Medical advice/attention if you feel unwell. If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

Skin Contact

Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes or until medical aid is available. Store contaminated clothing under water and wash before re-use or discard. If skin irritation occurs or you feel unwell: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Call a POISON CENTER/doctor if you feel unwell.

Eye Contact

If eye irritation persists: Get medical advice/attention. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face.

Ingestion

Rinse mouth. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call a POISON CENTER or doctor.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Fire will produce irritating gases. Contents under pressure. May be ignited by friction, heat, sparks or flames. Containers can explode in a fire. Containers exposed to heat and flames may rupture with violent force. Cylinders exposed to fire may vent and release gas through pressure relief devices. Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to source of ignition and flash back.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Spills

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE).

For small spills (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.

For large spills (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use. Avoid breathing vapor or mist. Use good personal hygiene practices. Eating, drinking and smoking in work areas is prohibited. Remove contaminated clothing and protective equipment before entering eating areas. All containers must be properly labelled. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Eyewash stations and showers should be available in areas where this material is used and stored. Do not get in eyes, on skin, or on clothing.

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source. Report ventilation failures immediately.

Storage Room Requirements

Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Store in approved containers and protect against physical damage. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity during transfer by ground and bonding containers and equipment before transferring material. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)
CYCLOHEXANE		CNS impair; eye & URT irr		300	1050			1
DIETHYL HYDROXYLAMINE		URT irr						
DIFLUOROETHANE	A4	Bone dam; fluorosis	A4; BEI		2.5			1

Chemical Name	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)
HEXANE		CNS impair; peripheral neuropathy; eye irr	Skin; BEI	500	1800			1
METHYL ACETATE		Headache; dizziness; nausea; eye dam (degeneration of ganglion cells in the retina)		200	610			1

Chemical Name	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen	ACGIH TWA (ppm)
CYCLOHEXAN E			300	1050				100
DIETHYL HYDROXYLAM INE								2
DIFLUOROETH ANE								
HEXANE			50	180				50
METHYL ACETATE			200	610	250	760		200

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
CYCLOHEXAN E			
DIETHYL HYDROXYLAM INE			
DIFLUOROETH ANE	2.5		
HEXANE			
METHYL ACETATE		250	

A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

The information in this Section does not list non-hazardous components that might have relevant NIOSH TWA (mg/m3), OSHA TWA (ppm), OSHA TWA (mg/m3) OSHA Tables (Z1, Z2, Z3) regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Density	6.35599 lb/gal
Specific Gravity	0.76162
VOC Actual(g/l)	469.93100 g/l
Density VOC	3.92165 lb/gal
% VOC	61.70000%
VOC Composite Partial Pressure	N/A
Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A

pH	N/A
Flammability	N/A
Water Solubility	N/A
Flash Point Symbol	N/A
Flash Point	N/A °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Evaporation Rate	N/A
Kinematic Viscosity	N/A
Kinematic Viscosity Temperature	N/A

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid heat, sparks, flame, high temperature, freezing and contact with incompatible materials. Avoid all possible sources of ignition.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Skin Corrosion/Irritation

0000110-54-3 HEXANE

The substance is irritating to the skin

0000110-82-7 CYCLOHEXANE

May affect the central nervous system. May damage the liver and kidneys.

Serious Eye Damage/Irritation

Causes serious eye irritation

0000110-82-7 CYCLOHEXANE

Can irritate and burn the skin.

Respiratory/Skin Sensitization

0000110-82-7 CYCLOHEXANE

Can irritate and burn the eyes.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Suspected of damaging fertility or the unborn child

0000110-54-3 HEXANE

Animal tests show that this substance possibly causes toxic effects upon human reproduction.

Specific Target Organ Toxicity - Single Exposure

May cause drowsiness or dizziness

0000110-82-7 CYCLOHEXANE

Exposure can cause headache, dizziness and lightheadedness.

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

0000110-54-3 HEXANE

Repeated or prolonged contact with skin may cause dermatitis. The substance may have effects on the central nervous system and peripheral nervous system. This may result in polyneuropathy.

Aspiration Hazard

May be fatal if swallowed and enters airways

0000110-54-3 HEXANE

ASPIRATION causes severe lung irritation, coughing, pulmonary edema; excitement followed by depression.

Acute Toxicity

May be harmful if swallowed

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is 4464.29 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is >20 mg/l

The Acute Toxicity Estimate (ATE) for an inhalation (dust and mist) exposure to this mixture is >5 mg/l

0000110-54-3 HEXANE

INHALATION causes irritation of respiratory tract, cough, mild depression, cardiac arrhythmias. It has been reported that a 10 minute exposure to 5,000 ppm caused dizziness and a sensation of giddiness INGESTION causes nausea, vomiting, swelling of abdomen, headache, depression.

Chronic Exposure

Based on available data, the classification criteria are not met.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

0000110-54-3 HEXANE

The substance can be absorbed into the body by inhalation of its vapour and by ingestion.

0000110-82-7 CYCLOHEXANE

Mildly irritating to the respiratory tract. If swallowed, aspiration into the lungs may result in chemical pneumonitis.

Potential Health Effects - Miscellaneous

Based on available data, the classification criteria are not met.

0000110-82-7 CYCLOHEXANE

LD50 (oral, rat): 8-39 mL/kg (6200 to 30400 mg/kg) (3)

LD50 (oral, mouse): 1300 mg/kg (3)

LD50 (dermal, rabbit): Greater than 18000 mg/kg (4)

0000110-54-3 HEXANE

LC50 (male rat): 38500 ppm (4-hour exposure); cited as 77000 ppm (271040 mg/m3) (1-hour exposure) (15)

LC50 (rat): 48000 ppm (4-hour exposure) (16)

LC50 (rat): 73680 ppm (260480 mg/m3) (4-hour exposure) (n-hexane and isomers) (1,3)

LD50 (oral, 14-day old rat): 15840 mg/kg (3)

LD50 (oral, young rat): 32340 mg/kg (3)

LD50 (oral, adult rat): 28700 mg/kg (3,16)

0000079-20-9 METHYL ACETATE

LC50 (rat): 16000-32000 ppm (4-hour exposure) (9)

LD50 (oral, rat): greater than 5000 mg/kg (4)

LD50 (oral, rabbit): 3700 mg/kg (cited as 50 millimols/kg) (10)

LD50 (skin, rabbit): greater than 5000 mg/kg (4)

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

0000110-82-7 CYCLOHEXANE

Readily biodegradable

Persistence and Degradability

0000110-54-3 HEXANE

Readily biodegradable in water.

0000110-82-7 CYCLOHEXANE

Readily biodegradable

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000110-54-3 HEXANE

The substance is not PBT / vPvB.

0000110-82-7 CYCLOHEXANE

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws. It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)

UN/NA #: UN1950

Hazard Class: 2.1
Required Mark: Limited Quantity

IMDG Information

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)
UN/NA #: UN1950
Hazard Class: 2.1
Required Mark: Limited Quantity
Marine Pollutant: No data available

IATA Information

Shipping Name: Aerosols, flammable, (each not exceeding 1 L capacity)
UN/NA #: UN1950
Hazard Class: 2.1
Required Mark: Limited Quantity

SECTION 15) REGULATORY INFORMATION

CAS	Chemical Name	% By Weight	Regulation List
0000110-54-3	HEXANE	10% - 30%	SARA313, Canada_NPRI, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, HAPS, SARA312, OC_HAPS, VOC, TSCA - Toxic Substances Control Act (TSCA), NEI - National Emissions Inventory, CA_Prop65, CA_Prop65_Type_Toxicity_Male - CA_Proposition65_Type_Toxicity_Male, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000115-10-6	METHYL ETHER	10% - 30%	DHS_COI - DHS_Chemical Of Interest, Canada_NPRI, DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0000075-37-6	DIFLUOROETHANE	10% - 30%	DHS_COI - DHS_Chemical Of Interest, DSL - Domestic Substance List, SARA312, VOC_exempt, TSCA - Toxic Substances Control Act (TSCA), NEI - National Emissions Inventory, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL)
0220543-67-9	Cyclopentene, polymer with 1-butene, (2E)-2-butene, (2Z)-2-butene, 2-methyl-1-propene and 1,3-pentadiene	7% - 13%	NDL - Non-Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA), TSCA_PMN - TSCA Pre-manufacture Notices (PMNs)
0000110-82-7	CYCLOHEXANE	5% - 10%	SARA313, Canada_NPRI, DSL - Domestic Substance List, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0025038-32-8	Isoprene-Styrene Polymer	5% - 10%	DSL - Domestic Substance List, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000079-20-9	METHYL ACETATE	1.00% - 5%	DSL - Domestic Substance List, SARA312, VOC_exempt, TSCA - Toxic Substances Control Act (TSCA), NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), MA_RightToKnow - Massachusetts Right to Know
0003710-84-7	DIETHYL HYDROXYLAMINE	0.10% - 1.00%	DSL - Domestic Substance List, SARA312, VOC, TSCA - Toxic Substances Control Act (TSCA)

The information in this Section does not list non-hazardous components that might have relevant MA_RightToKnow - Massachusetts Right to Know, NJ_RightToKnow_HazSubList - New Jersey Right to Know Hazardous Substance List (RTKHSL), SARA312, DSL - Domestic Substance List regulatory values, if they are present at less than 1%. Please contact manufacturer for more information.



WARNING: This product can expose you to chemicals including HEXANE, which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16) OTHER INFORMATION

General

GHS Revision 7 - Prescribed Ranges


Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL - Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

HMIS

Health	1 / 2
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	B

NFPA



(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 2.0:

Revision Date: Jun 17, 2026

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.