



LED TEMPORARY WORK SITE LIGHTS

Models

LED-9006-50K	60W Work Light with 20' power cord
LED-9010-50K	100W Work Light with 35' power cord
LED-9015-50K	150W Work Light with 35' power cord

Features

- Work Lights are easy to install and offer a flexible solution for temporary lighting
- Operates on 120/277 volt power, and includes a 20' to 35' long power cord. Operates on 277VAC with jumper cable.
- Lamps can easily be daisy chained to cover large areas
Up to 10 of the LED-9006 fixtures or up to 6 of the LED-9010 fixtures or a combination of the two, not exceeding 600W
- Includes remote control
- IP 64 rated - suitable for damp locations
- 5 Year Warranty
18 gauge wire with 105C rating, type SJTW.



TECHNICAL SPECIFICATIONS

MODEL	VOLTAGE	WATTAGE	LUMENS	LPW	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-9006-50K	120/277VAC	60W	6,600	110	250W HID	20' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO
LED-9010-50K	120/277VAC	100W	11,000	110	400W HID	35' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO
LED-9015-50K	120/277VAC	150W	16,500	110	600W HID	35' power cord	5000K	>80	<20%	>0.9	N/A	N/A	360°	NO

PACKAGING SPECIFICATIONS

MODEL	PRODUCT DIMENSION	PRODUCT WEIGHT	UNIT CARTON DIMENSION	UNIT CTN WT	SHIPPER CARTON DIMENSION	SHIPPER CTN WT	CARTON QUANTITY
LED-9006-50K	6.5" dia. X 10.8" tall	4.0 lbs	12.8" x 8.5" x 8.2"	4.0 lbs	17.5" x 13.4" x 17.3"	16.5 lb	4
LED-9010-50K	6.5" dia. X 12.2" tall	4.2 lbs	14.5" x 8.5" x 8.2"	4.2 lbs	17.5" x 15.0" x 17.3"	17.3 lb	4
LED-9015-50K	6.5" dia. X 13.7" tall	4.4 lbs	15.5" x 8.5" x 8.2"	4.4 lbs	17.5" x 16.1" x 17.3"	18.1 lb	4

UPC / UCC




DESIGN LIGHTS CONSORTIUM QPL CERTIFICATION SUMMARY

MODEL	PRODUCT UPC	CARTON UCC	QPL CATEGORY 1	PRODUCT CODE	FAMILY CODE	QPL CATEGORY 2	PRODUCT CODE	FAMILY CODE
LED-9006-50K	8440060 9103 3	10 8440060 9103 0	N/A	N/A	N/A	N/A	N/A	N/A
LED-9010-50K	8440060 9104 0	10 8440060 9104 7	N/A	N/A	N/A	N/A	N/A	N/A
LED-9015-50K	8440060 9105 7	10 8440060 9105 4	N/A	N/A	N/A	N/A	N/A	N/A

ENERGY SAVINGS VS. HID

NOTES

Mounting Orientation

	LED-9006-50K	LED-9010-50K		BASE DOWN	BASE UP	HORIZONTAL	
LED Lamp Power (watts)	60	100	<p>Note: Each light comes with 1 remote control. The remote control will operate any lights within a range of about 25 feet. If the remote control is misplaced, the lights can be reset by disconnecting them for 20 seconds. When they are reconnected, the lights will come on.</p> <p>Specifications are subject to change without notice.</p>				
HID Lamp Power (watts)	250	400		NOT APPROVED	APPROVED	NOT APPROVED	
HID Ballast Power (watts)	37.5	60		THERMAL SPECIFICATIONS			
Total power Savings (watts)	227.5	360		Recommended Minimum Fixture Size	OPERATING TEMPERATURE		-40°F to +122°F
Annual Energy Savings	\$128	\$202		Width	IN-SITU TEMP MEASUREMENT/L70		
Lifetime Energy Savings over 50,000 hrs)	\$1,251	\$1,980		Height	LED TEMPERATURE*		N/A
			Volume (Cu. In.)	L70 LED LUMEN MAINTAINANCE*		>50,000	