



844-pik-fast • www.pik-fast.com

PRODUCT DATA SHEET

FM670 - Tuff Tape III Banner Hemming Tape

Description:

Our tape is ideal for making "instant" banner hems. The Tuff Tape III is resistant to water, moisture, and temperature fluctuations. It offers an excellent bond for many substrates such as vinyl fabrics, aluminum, brass, wood, and plastics.

Features:

- Clear tape on white paper liner
- Suitable for outdoor use
 - Withstands temperature variations
 - Water and moisture resistant
- Good UV resistance
- Available in die cut form (FM670D)

- Ⓞ FM670-.5 1/2" x 36YD
- Ⓞ FM670-1 1" x 36YD
- Ⓞ FM670-1.5 1 1/2" x 36YD
- Ⓞ FM670-2 2" x 36YD



Product Data			
Carrier	Polypropylene	1.2 mil	0.03 mm
Adhesive (each side)	Acrylic	3.5 mil	0.09 mm
Liner	White glassine paper	3.0 mil	0.08 mm
Total Tape Thickness	-	11.2 mil	0.29 mm
Peel Adhesion	From Stainless Steel	80 oz/in	22 N/25 mm
Temperature Resistance	-	200°F	93°C
Recommended Industry	Framing	Awards	Signs Trophies

Application Notes:

Plasticizer resistant tape commonly used for hemming vinyl banners in the sign industry. Cut into thin widths (~1/8"), it is used as a fillet tape in the framing industry. Aggressive and durable adhesive makes it a great all-around tape that can be used in many applications that require a double-sided tape.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity