


NOTES:

1. INLET: 5/16" BARB
2. OUTLETS: 5/16" BARB W/ SHUTOFF
3. GAUGES: 60# (4 EA)
4. SAFETY BLOW-OFF: 60 ± 5 PSI
5. WORKING PRESSURE: 0-50 PSI
6. POLY BONNETS WITH ADJ GOLD CAPS

MATERIAL	NAME	DATE	 <p>248 NORTHWESTERN DR SAN ANTONIO TX 78239</p>
	DRAWN	JRS	
FINISH	ENG APPR.	PF	
DIMENSIONS ARE IN INCHES			<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASCO MFG., INC. IS PROHIBITED.</p>
TOLERANCES:			
FRACTIONAL ± 1/64			
ANGULAR: MACH ± 1/2°			
BEND ±			<p>TITLE:</p> <p>REG BEER PNL, 4P4P, 4Y, JUMPR, 60" 5/16B IN/SHTFF, CO2 TBG, 21" X 8.5"</p>
TWO PLACE DECIMAL ± 0.015			<p>SIZE DWG. NO.</p> <p>B T1694STWMK-01_SALES</p>
THREE PLACE DECIMAL ± 0.005			<p>REV</p> <p>C</p>
			<p>SCALE: 1:2</p> <p>DO NOT SCALE DRAWING</p>
			<p>SHEET 1 OF 1</p>