

M1S7564



15GA Medium Crown Stapler

Applications

Crate Assembly, Pallet Assembly



Specifications

Fastener Crown	1/2"
Fastener Length	1-1/2" - 2-1/2"
Magazine Capacity	138
Actuation Mode	Selective Actuation
Dimensions	14-1/2" x 4-1/2" x 10-1/2"
Weight	5.9 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.062 SCF
Noise Power Emissions per EN12549 LwA,1s	100.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	90.5 dBA
Vibration Emissions per ISO-8662-11	4.80 m/s ²
Vibration Value Uncertainty per ISO-8662-11	0.97 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Heavy Duty, Quick Clear Nose, Top Load Aluminum Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessories

Air Filter (P-97454), Full Sequential Actuation Trigger (AS-21037), Long Magazine (M1S7564LM)

For Best Results, Use Spotnails® Collated Fasteners

15GA 1/2" Medium Crown Staples
(Similar to Bostitch® BCS15S4)

STOCK No.	LENGTH	M/BX	Bx/Cs
-----------	--------	------	-------

Galvanized

7512PG-10.3M	1-1/2"		
7514PG-8.4M	1-3/4"		
7516PG-4.5M	2"		
7516PG-7.7M	2"		
7520PG-6.2M	2-1/2"		

304 Stainless Steel

7516PS-4.5M	2"		
-------------	----	--	--

15.5GA 1/2" Medium Crown Staples

Galvanized

7516PG-5M-15.5	2"		
7516PG-6M-15.5	2"	1	6