IMPRONTA STONE MIX

THRU-BODY PORCELAIN, FULL COMMERCIAL & RESIDENTIAL







Nominal Sizes



12x24 - Non-Rectified



Colours



Striato White



Quarzite Grey



Travertino Cream



Ardesia Black

Recommended applications

Neconinented applications				
Residential	Bath / Shower	Wall		
Light commercial	Fireplace	Floor		
Medium commercial	Outdoor	Indoor		
Heavy commercial				

Characteristics of tile

characteristics or ti		
Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Eco-friendly	Odour resistant
Hypnallergenic		

Technical specifications

recrimear specimea	CIOIIS		
CGSB Type	7	монѕ	n/a
PEI	n/a	Tile thickness	10 mm
Dynamic Coefficient of Friction	> 0.42	Chemical Resistance	Class UA
Friction Coefficient	Wet: ≥ 0.6 Dry: ≥ 0.7	Variation	V1
Frost Resistance	Yes		Moderate Substantial
Water Absorption	0.1%	SEEN BUILD	

Special instructions

■ Shade variations between tiles is characteristic. Colour may vary from sample. For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.





www.TierraSol.ca