

T1B1840



18GA Brad Nailer

Applications

Cabinet Assembly, Door & Window Manufacturing,
Drawer Assembly, Finish Carpentry, Furniture Assembly,
Hardwood Flooring, Trim Molding



Specifications

Fastener Length	5/8" - 1-9/16"
Magazine Capacity	100
Actuation Mode	Selective Actuation
Dimensions	9" x 2-1/2" x 8-1/4"
Weight	3.0 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.016 SCF
Noise Power Emissions per EN12549 LwA,1s	96.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	86.9 dBA
Vibration Value Less than 2.5 m/s ² per ISO-8662-11	
Vibration Value Uncertainty per ISO-8662-11	0.73 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control,
Ergonomic Rubber Grip, Quick Clear Nose,
Rear Load Steel Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessory

Full Sequential Actuation Trigger (AS-21040)

For Best Results, Use Spotnails® Collated Fasteners

18GA Brads AX Type

STOCK No.	LENGTH	M/ Bx	Bx/ Cs	STOCK No.	LENGTH	M/ Bx	Bx/ Cs
Galvanized				1M Clamshell Pack-Galvanized			
18510	5/8"	5	20	18116	1"	1	8
18512	3/4"	5	20	18119	1-3/16"	1	8
18516	1"	5	10	18120	1-1/4"	1	8
18519	1-3/16"	5	10	1M Clamshell Pack 304 Stainless Steel			
18520	1-1/4"	5	10	18116SS-8M	1"	1	8
18522	1-3/8"	5	10	18120SS-8M	1-1/4"	1	8
18525	1-9/16"	5	10	1M Clamshell Pack 316 Stainless Steel			
304 Stainless Steel				18116SS-8M-316	1"	1	8
18516SS	1"	5	10	18120SS-8M-316	1-1/4"	1	8
18520SS	1-1/4"	5	10				
316 Stainless Steel							
18516SS-316	1"	5	10				
18520SS-316	1-1/4"	5	10				