

RC1016



Corrugated Fastener Tool

Applications

Furniture Assembly, Hollow Core Doors, Pallet Repair, Stringer Repair, Truss Manufacturing



Specifications

Fastener Crown	1"
Fastener Length	1/4" - 5/8"
Magazine Capacity	120
Actuation Mode	Full Sequential Actuation
Dimensions	14-1/2" x 2-1/4" x 10-1/4"
Weight	4.7 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.035 SCF
Noise Power Emissions per EN12549 LwA,1s	108.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	106.1 dBA
Vibration Emissions per ISO-8662-11	3.48 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Narrow Body to Fit Between Pallet Slates, Top Load Aluminum Magazine

Includes

Allen Wrenches, Contact Actuation Trigger, Safety Glasses, Tool Case, Tool Oil

Accessory

Air Filter (P-97454)

For Best Results, Use Spotnails® Collated Fasteners

Stock No.	LENGTH	M/Cs
416	1/4"	15.8
416-8M	1/4"	8.0
616	3/8"	11.0
616-5M	3/8"	5.0
816	1/2"	8.4
816-4M	1/2"	4.0
1016-3.4M	5/8"	3.4

Short Strip

CORR-W9-9.21M	3/8"	9.21
CORR-W12-6.91M	1/2"	6.91