



100# GAUGE

160# GAUGE

2000# GAUGE

1/4" FLARE

1/4" FLARE WITH CHECK

1/4 FLARE (F)
SWIVEL

6 FT HOSE

CGA 320 TANK FTG
AND NUT

NOTES:

1. INLET: 1/4" FLARE (6' HOSE WITH TANK FTGS)
2. OUTLETS: 1/4" FLARE WITH CHECK (2 EA)
3. GAUGES: 160#, 100#, 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, RED

MATERIAL	NAME	DATE
	DRAWN	EG 06/04/10
FINISH	ENG APPR.	
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2° BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



TITLE: **REG PR WM, 2P2P, 100/160, 6' HOSE CGA 320 FTG/ NUT, 1/4F, 2K, RED CAPS**

SIZE	DWG. NO.	REV
A	T8861-6_SALES	B

SCALE: 1:1 DO NOT SCALE DRAWING SHEET 1 OF 1