



PROJECT:	MODEL:	QUANTITY:	ITEM NO:

# PROOFER & HEATED HOLDING CABINETS

## Insulated - Various Size Trays, Pans and Gastro-Norm

### PROOFER "PH-1826" SERIES

Two cabinets in one! Dual-purpose cabinets proof and heat - eliminating costly duplication of equipment.



PH-1826-18  
Shown with optional Lexan Door

- 1 Easy to use - upfront and recessed control panel has separate, easy to read and set, air moisture and air temperature controls
- 2 Standard recessed Antimicrobial SaniGuard door handle - detains illness causing pathogens
- 3 Built-in humidity system balances moisture and air with controlled heat and humidity capabilities - allows for greater control of holding food environment for longer holding periods
- 4 Removable humidity pan: 12" x 20" pan provides large water reservoir - removable, easy to clean and replaceable
- 5 Removable and adjustable tray slides - designed to protect dough during proofing cycle.
- 6 Constructed of stainless steel, with welded base frame for added strength and durability - fully insulated cabinet and door provide energy efficient heating and longer holding times
- 7 Field reversible door - flexible installation options for kitchen layout

**\*Two year limited warranty**



PH-1826-7



Control Panel



Antimicrobial SaniGuard Handle



Humidity Pan




Adjustable Tray Slides



PROJECT:	MODEL:	QUANTITY:	ITEM NO:
----------	--------	-----------	----------


# SPECIFICATIONS: PROOFER/HEATED HOLDING CABINETS



ELECTRICAL DATA					
	PH-1826-7 PH-1826-14 PH-1826-15 PH-1826-18		OPTIONAL Heating Element 1750w	PH-1826-7-7 Split Cavity	
VOLTS	120	220-240	120	120	220-240
WATTS	1650	2133	2150	2300	3075
AMPS	13.75	8.9	18	19.2	12.8
HERTZ	50/60	50/60	50/60	50/60	50/60
PHASE	Single	Single	Single	Single	Single
PLUG USA	5-15P	6-15P	5-20P	5-20P	6-15P
PLUG CANADA	5-20P	6-15P	5-30P	5-30P	6-20P

Dedicated circuit.

MODEL NUMBER	STANDARD CAPACITY @ 4.5" Spacings (114 mm)					OPTIONAL CAPACITY @ 3" Spacings (76 mm)					OVERALL EXTERIOR DIMENSIONS IN. (mm) (Height Includes Casters)			CLASS 100				
	TRAY/PAN SLIDES PROVIDED	18 x 26		12 x 20		TRAY/PAN SLIDES REQUIRED (Additional)	18 x 26		12 x 20		HIGH "H"	DEEP "D"	WIDE "W"	NO. OF DOORS	CASTER SIZE	SHIP WT. (KG)		
		Baguette	GN 1/1	Baguette	GN 1/1		Baguette	GN 1/1										
PH-1826-7 Under Counter	5 pr	5	5	5	10	5	7 pr (2 pr)	7	7	7	14	7	32.5" (826)	31.5" (800)	27.25" (692)	1	2**	220 (100)
PH-1826-14	10 pr	10	10	10	20	10	14 pr (7 pr)	14	14	14	28	14	36.5" (927)	31.5" (800)	49.5" (1258)	2	5"	320 (145)
PH-1826-15	10 pr	10	10	10	20	10	15 pr (5 pr)	15	15	15	30	15	60.5" (1537)	31.5" (800)	27.25" (692)	1	5"	280 (127)
PH-1826-18	12 pr	12	12	12	24	12	18 pr (6 pr)	18	18	18	36	18	69.25" (1759)	31.5" (800)	27.25" (692)	2	5"	285 (129)
PH-1826-7-7 Split Cavity	10 pr (5 ea)	10	10	10	20	10	14 pr (4 pr)	14	14	14	28	14	69.25" (1759)	31.5" (800)	27.25" (692)	2	5"	390 (177)



DOOR SWING: 180°

**[A]** Tray-slides accommodate: (1) 18" x 26", (1) 12" x 20", (2) 14" x 18", (1) GN 1/1 trays and / or pans. Universal tray slides are adjustable. Number of tray slides are listed above. Standard spacings are 4.5" (114 mm). Uprights punched on 1.5" (38 mm) centers.  
 • Dutch Doors ["D"] are 2 half size doors on full-size models.  
 • Pass-thru Door [add "P"] is available on all model sizes.  
 • See-thru Lexan Door [add "L"] is available on all model sizes.  
 PH-1826-7-7 Split Cavity Capacity: Total number of trays/pans for both cavities combined.  
 \*PH-1826-7 is standard with all swivel casters.

**CONSTRUCTION.** Helicarc welded, single unit construction of stainless steel; 20-gauge polished exterior, 22-gauge stainless steel interior with easy-to-clean covered corners. Welded tubular base frame shall be 1" square, heavy gauge stainless steel tubing, with 10-gauge stainless steel reinforcing plates at corners and fittings.  
**INSULATION.** "Ultra-Guard" UG-26 high density fiberglass insulation throughout; top, back, bottom, sides and door(s).  
**HANDLES.** Form grip flush-in-wall hand grips recess mounted on each side of unit.  
**DOORS AND LATCHES.** Flush mounted, field reversible, stainless steel insulated doors. High temperature gasket sealed; gasket shall be cabinet mounted. Each door shall have two (2) heavy duty edgemoat die cast hinges and an Antimicrobial SaniGuard door handle. The hinge mountings are reinforced with stainless steel backing plates. PH-1826-14 model is not available with field reversible doors.

**CASTERS.** Maintenance free polyurethane tire casters in a configuration of two (2) rigid and two (2) swivel with brake. PH-1826-7 model shall be standard with a caster configuration of four (4) swivel with brake. Casters shall have a reinforced yoke mounted to 10-gauge caster plate. The caster mounting plate shall be secured to a 10-gauge stainless steel reinforcing stress plate via welded in place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular frame of the unit.  
**TRAY SLIDES.** Welded rod-style tray slides are stainless steel for greater durability and sanitation. Fully adjustable / removable and designed to give secure bottom tray support. Tray-slides accommodate: (1) 18" x 26", (1) 12" x 20", (2) 14" x 18", (1) GN 1/1 trays and / or pans. Removable stainless steel uprights shall be punched on 1.5" (38 mm) spacings for easy tray adjustment, and shall easily lift off heavy-duty stainless steel brackets without the use of tools for cleaning.

**PROOFER/HEATER SYSTEM AND CONTROLS.** System shall include two (2) separate long life Incoloy nickel chromium alloy heating elements; separate, adjustable controls shall be provided for each function: One to control the interior air temperature, and one to control the interior air moisture. A stainless steel water reservoir shall be removable for ease of cleaning/sanitation. System shall have a Hi-temp, self-lubricated, impedance protected fan-cooled blower motor for moist air distribution. Controls shall include adjustable air temperature control (to 190°F.), adjustable moisture control (Low to High), 20 amp ON/OFF power switch, operational range thermometer.

**ELECTRICAL CHARACTERISTICS.** 3 wire grounded 10 foot extension power cord and plug. See electrical data chart above for amperage and receptacle configuration. Dedicated circuit.  
**INSTALLATION.** Unit should not be installed in an area where adverse environmental conditions are present.

- Optional Accessories**
- ELECTRICAL**
- Electronic controls
  - 220 volt, 50/60 Hz single phase
  - Timer, available with manual controls only
  - Element upgrade
- DOORS**
- Dutch doors
  - See-thru Lexan door
  - Key locking door latch
  - Paddle latch
  - Left hand door hinging
  - Glass doors
- SPACINGS**
- Extra stainless steel tray slides
  - Fixed rack
- CASTERS**
- All swivel or larger casters
- EXTRAS**
- Top corner bumpers (set of 4)
  - Security packages
  - Full extension bumper
  - Heavy-duty push/pull handles

FWE products may be covered under one or more of the following U.S. patents: 288,299;238,300;3,952,609;4,192,991. All rights reserved. All specifications subject to change without notice. Errors subject to correction.  
 © 15 Food Warming Equipment Company, Inc. R.15.02



**FOOD WARMING EQUIPMENT COMPANY, INC.**  
 5599 HWY. 31 W. Portland, TN 37148  
 800.222.4393 | 815.459.7500 | Fax: 815.459.7989  
 www.FWE.com | sales@fwe.com

COOK | HOLD | TRANSPORT | SERVE | REFRIGERATION | BARS

