

M1T9764



T-Nailer

Application

Lathing to Concrete

Specifications

Fastener Diameter	.097
Fastener Length	5/8" - 2-1/2"
Magazine Capacity	80
Actuation Mode	Full Sequential Actuation
Dimensions	15" x 4-1/2" x 10-1/2"
Weight	5.9 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.062 SCF
Noise Power Emissions per EN12549 LwA,1s	100.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	90.5 dBA
Vibration Emissions per ISO-8662-11	4.80 m/s ²
Vibration Value Uncertainty per ISO-8662-11	0.97 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Side and Top Load Steel Magazine

Includes

Allen Wrenches, Contact Actuation Trigger, Safety Glasses, Tool Case, Tool Oil

Accessory

Air Filter (P-97454)



**For Best Results, Use
Spotnails® Collated Fasteners**

.097 T-Nails

STOCK No.	LENGTH	M/Bx	Bx/Cs
Hardened Galvanized			
T09710HG	5/8"	2.5	4

RELIABILITY
Provin

Division of Peace Industries, LTD.

P: 800-873-2239 / 847-259-1620 | F: 888-369-2588 | customerservice@spotnails.com
SPOTNAILS.BIZ | SPOTNAILS.COM | RELIABILITYPROVIN.COM

Jan. 2022