IRIS US BLOCKS 5.0

GLAZED PORCELAIN

USA only

tierra sol

Nominal Sizes

12x24 Honed

50/50

Special Order: 18x36, Lappato finish available

Colors

White

Grey

Rust

Dark



Wood

Decors and Special Pieces

2x2 Mosaic - Honed

12x12 Sheet

4x24 Bullnose

Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	Outdoor

Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

Technical specifications

CGSB Type	7	MOHS	≥ 7
PEI	White, Grey, Wood: 4 Dark, Rust: 3	Tile thickness	9 mm
Dynamic Coefficient of Friction	Wet: ≥ 0.42	Chemical Resistance	Class A
Friction Coefficient	Wet: ≥ 0.6 Dry: ≥ 0.75	Variation	V1 V2 V3 V4 Moderate
Frost Resistance	Yes		
Water Absorption	≤ 0.1%		

Special instructions

- Shade variations between tiles is characteristic. Color may vary from sample.
- For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

www.TierraSol.ca