



NOTES:

1. INLET: 5/16" BARB
2. OUTLET: 5/16" BARB W/SHUT-OFF (5 PLCS)
3. GUAGES: 60# (5 PLCS)
4. SAFETY BLOW-OFF 60 ± 5 PSI.
5. WORKING PRESSURE: 0-50 PSI
6. BONNET: POLY, GOLD
7. S/S BEER "Y" BRACKET (5 PLCS) & 26" PANEL

MATERIAL	NAME	DATE
	DRAWN	JRS 11/11/10
FINISH	ENG APPR.	PF 10/10/11
	PROPRIETARY AND CONFIDENTIAL	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1/2" BEND ± TWO PLACE DECIMAL ± 0.015 THREE PLACE DECIMAL ± 0.005		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.		



3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238

TITLE:
**REG SEC BEER ,5P5P, 60#,
 5/16B IN, 5/16B SHUTOFF,
 POLY GOLD, 26" PNL**

SIZE	DWG. NO.	REV
A	T1695STWMK_SALES	C

SCALE: 1:3 DO NOT SCALE DRAWING SHEET 1 OF 1