


**NOTES:**

1. INLET: 1/4" FLARE
2. OUTLET: 1/4" FLARE WITH CHECK VALVE
3. GAUGE: 60#
4. SAFETY BLOW-OFF: 130 ± 4 PSI
5. WORKING PRESSURE: 0-125 PSI
6. POLY BONNET WITH GOLD ADJ. CAP

|  |  |      |  |
|--|--|------|--|
| MATERIAL   | NAME   | DATE | <br>3248 NORTHWESTERN DR. SAN ANTONIO, TX 78238 |
|  | DRAWN  | JPK  |  |
| FINISH   | ENG APPR.  |      | TITLE:   |
|  | <b>PROPRIETARY AND CONFIDENTIAL</b><br>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED. |      | <b>REG, SEC, SODA, 60#, 1/4F IN, 1/4F-CV OUT, POLY, GOLD</b>   |
| DIMENSIONS ARE IN INCHES<br><br>TOLERANCES:<br>FRACTIONAL ± 1/64<br>ANGULAR: MACH ± 1/2°<br>BEND ±<br>TWO PLACE DECIMAL ± 0.015<br>THREE PLACE DECIMAL ± 0.005 | DWG. NO.<br><b>A T5261SN60_SALES</b>   |      | REV<br><b>A</b>  |
|  | SCALE: 1:2   |      | DO NOT SCALE DRAWING   |
|  |  |      | <b>SHEET 1 OF 1</b>  |