

# EDILGRES E-STREET ARCH

UNGLAZED PORCELAIN

tierra sol

A sophisticated and modern interpretation of cement is blended in a balanced mix of graphics and colours, turning it into a minimal and versatile surface, suitable for any style and type of environment.



## Nominal Sizes

24x24 Natural


24x24 Polished

Special Order: 24x48 Natural, 12x24 Natural


## Colours




Ice




Sand



Grey



Smoke



Graphite

## Decors and Special Pieces

Special Order:  
2.5x2.5 Mosaic (12x12 Sheet), 4x24 Bullnose Natural

## Recommended applications

Residential	Bath / Shower
Light commercial	Indoor
Medium commercial	Wall
Fireplace	Floor

## Characteristics of tile

Low maintenance	Fade resistant
Stain resistant	Hypoallergenic
Resistant to fungus	Odour resistant

## Technical specifications

CGSB Type	7	MOHS	n/a
PEI	n/a	Tile thickness	10 mm
Dynamic Coefficient of Friction - Natural	0.48	Chemical Resistance	Class UA
Friction Coefficient	n/a	Variation	V1  V2  V3  V4 Slight
Frost Resistance	Yes		
Water Absorption	≤ 0.5%		



## Special instructions

■ Shade variations between tiles is characteristic. Colour may vary from sample.



www.TierraSol.ca