



LED-9002-50K-5PK

Model

LED-9002-50K-5PK 20W Work Light 5 Pack with 10' power cords

Features

- Work Lights are easy to install and offer a flexible solution for temporary lighting.
- Operates on standard 120 volt power. Lights come in a permanently connected 5-light string with a 10' power cord.
- Total string length is 50'.
- IP65 rated - suitable for wet locations.
- Includes carrying bag.
- 3 Year Warranty



TECHNICAL SPECIFICATIONS

MODEL	VOLTAGE	WATTAGE	LUMENS	LPW	REPLACES	BASE	CCT	CRI*	THD*	PF*	R9*	Duv*	LIGHT DISTRIBUTION	DIMMABLE
LED-9002-50K-5PK	120VAC	100W (5X20W)	10000 (5X2000)	100	350W HID (5X70W)	10' POWER CORD AND 10' INTER-CONNECTION CORDS.	5000	>80	<20%	>0.9	N/A	N/A	360°	NO




PACKAGING SPECIFICATIONS

MODEL	PRODUCT DIMENSION	PRODUCT WEIGHT	UNIT CARTON DIMENSION	UNIT CTN WT	SHIPPER CARTON DIMENSION	SHIPPER CTN WT	CARTON QUANTITY
LED-9002-50K-5PK	4.25" dia X 7.0" tall	1.6 lb	14.25" X 14.25" X 8.1"	12.6 lb	14.25" X 14.25" X 8.1"	12.6 lb	1

UPC / UCC

DESIGN LIGHTS CONSORTIUM QPL CERTIFICATION SUMMARY

MODEL	PRODUCT UPC	CARTON UCC	QPL CATEGORY 1	PRODUCT CODE	FAMILY CODE	QPL CATEGORY 2	PRODUCT CODE	FAMILY CODE
LED-9002-50K-5PK	8440060 9102 6	10 8440060 9102 3	N/A	N/A	N/A	N/A	N/A	N/A

		Mounting Orientation		
		BASE DOWN	BASE UP	HORIZONTAL
LED Lamp Power (watts)	100			
HID Lamp Power (watts)	700	NOT APPROVED	APPROVED	NOT APPROVED
HID Ballast Power (watts)	105	THERMAL SPECIFICATIONS		
Total power Savings (watts)	705	Recommended Minimum Fixture Size		OPERATING TEMPERATURE
Annual Energy Savings	\$396	Width	N/A	-40°F to +122°F
Lifetime Energy Savings over 50,000 hrs)	\$3,878	Height	N/A	IN-SITU TEMP MEASUREMENT/L70
Specifications are subject to change without notice.		Volume (Cu. In.)	N/A	LED TEMPERATURE*
				L70 LED LUMEN MAINTAINENCE*
		>50,000		