

ABITARE SMART

COLOUR BODY GLAZED PORCELAIN

tierra sol



Nominal Sizes



24x24




12x24



Special Order:
24x24 Rectified,
12x24 Antislip

Colours



Ivory



Grey



Taupe



Black

Decors and Special Pieces

2x2 Mosaic



12x12 Sheet

Special Order:
3x24 Bullnose

Recommended applications



Residential



Light commercial



Medium commercial



Bath / Shower



Fireplace



Indoor



Wall



Floor



Outdoor

Characteristics of tile



Low maintenance



Stain resistant



Hypoallergenic



Fade resistant



Eco-friendly



Resistant to fungus



Odour resistant

Technical specifications



CGSB Type

7



PEI

4



Dynamic Coefficient of Friction

0.57



Friction Coefficient

n/a



Frost Resistance

Yes



Water Absorption

≤ 0.5%



MOHS

n/a



Tile thickness

24x24: 9 mm
12x24: 8.2 mm



Chemical Resistance

Minimum class
GB-UB



Variation

V1 V2 V3 V4
Slight



Special instructions

- Shade variations between tiles is characteristic. Colour may vary from sample.
- For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.



www.TierraSol.ca