

PS5016LN



20GA Fine Wire Long Nose Stapler

Applications

Insulation Installation, Picture Framing, Poly Sheeting,
Roofing Felt Installation, Screening, Upholstery



Specifications

Fastener Crown	1/2"
Fastener Length	1/4" - 9/16"
Magazine Capacity	84
Actuation Mode	Dual Trigger Actuation
Dimensions	8-1/4" x 2" x 8"
Weight	2.5 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.011 SCF
Noise Power Emissions per EN12549 LwA,1s	92.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	83.0 dBA
Vibration Emissions per ISO-8662-11	2.50 m/s ²
Vibration Value Uncertainty per ISO-8662-11	0.80 m/s ²

Features

Bottom Load Steel Magazine, Ergonomic Rubber
Grip, Fastener Supply Window, Front Exhaust

Includes

Air Fitting, Allen Wrenches, Tool Case, Tool Oil

For Best Results, Use
Spotnails® Collated Fasteners

1/2" Crown Fine Wire Staples
(Similar to Duo-Fast® 50)

STOCK No.	LENGTH	M/Bx	Bx/Cs
Galvanized, Chisel Point			
35504	1/4"	5	20
35505	5/16"	5	20
35506	3/8"	5	20
35508	1/2"	5	20
35509	9/16"	5	20
36505	5/16" DP	5	20

304 Stainless Steel

35504SS	1/4"	20	100
35506SS	3/8"	20	100
35508SS	1/2"	20	100
36504SS	1/4" DP	20	100
36506SS	3/8" DP	20	100
36508SS	1/2" DP	20	100