

# X1C1016



## Corrugated Fastener Tool

### Applications

Furniture Assembly, Hollow Core Doors, Pallet Repair, Truss Manufacturing



### Specifications

Fastener Crown	1"
Fastener Length	1/4" - 5/8"
Magazine Capacity	120
Actuation Mode	Full Sequential Actuation
Dimensions	14-1/2" x 3" x 10-1/4"
Weight	5.10 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	3/8"
Air Consumption per Cycle @ 90 PSI	0.042 SCF
Noise Power Emissions per EN12549 LwA,1s	106.5 dBA
Noise Pressure Emissions per EN12549 LpA,1s	105.0 dBA
Vibration Emissions per ISO-8662-11	3.39 m/s <sup>2</sup>
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s <sup>2</sup>

### Features

360° Adjustable Exhaust, Adjustable Depth Control, Ergonomic Rubber Grip, Quick Clear Nose, Top Load Aluminum Magazine

### Includes

Allen Wrenches, Contact Actuation Trigger, Safety Glasses, Tool Case, Tool Oil

### Accessories

Air Filter (P-97454), Walking Stick Attachment (AS-99105)

### For Best Results, Use Spotnails® Collated Fasteners

#### Corrugated Fasteners

Stock No.	LENGTH
416	1/4"
416-8M	1/4"
616	3/8"
616-5M	3/8"
816	1/2"
816-4M	1/2"
1016-3.4M	5/8"

#### Short Strip

CORR-W9-9.21M	3/8"
CORR-W12-6.91M	1/2"