



6FT HP HOSE



CO2 TANKT FTG WITH CGA 320 NUT



**NOTES:**

1. INLET: 1/4" FLARE
2. OUTLETS: 1/4" FLARE W/ CHECK
3. GAUGES: 160#, 2000#
4. SAFETY BLOW-OFF: 130 ± 4 PSI.
5. WORKING PRESSURE: 0-120 PSI
6. BONNETS: POLY, RED CAPS
7. UL252: SERIES 5740

MATERIAL	NAME	DATE
	DRAWN EG	06/04/10
FINISH	ENG APPR.	PF
	<b>PROPRIETARY AND CONFIDENTIAL</b>	
<p>DIMENSIONS ARE IN INCHES</p> <p>TOLERANCES:          FRACTIONAL ± 1/64          ANGULAR: MACH ± 1/2°          BEND ±          TWO PLACE DECIMAL ± 0.015          THREE PLACE DECIMAL ± 0.005</p>		
<p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPRITE-FASSCO MFG., INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPRITE-FASSCO MFG., INC. IS PROHIBITED.</p>		



TITLE:		
REG. SEC. SODA WM, 160#, 1/4F IN, 1/4F-CV OUT, 2000#, POLY BONNET, RED, 6' HOSE		
SIZE	DWG. NO.	REV
A	T5741WMHP-6_SALES	A
SCALE: 1:1	DO NOT SCALE DRAWING	SHEET 1 OF 1