



HOT WATER PRESSURE WASHER

OIL / DIESEL FIRED



Adjustable thermostat
up to 200°F

Stainless-steel coil skin provides extra durability and resists corrosion

HEATING COIL

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends, 5500 PSI rated full sized 126' length for proper heat production

Pressure Relief Valve protects the machine from over pressured expansion

ABC oil fired Beckett burner

14 gallon removable, rust-proof polyethylene gas and diesel tanks with gauge

Marine sealed battery box with 80 AH AGM deep cycle battery

Mounting bracket for truck mounting

Honda GX690 electric start w/ 17 amp charge

Engine / pump mounted on isolation pad to eliminate vibration

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame.

12" oil drain hose for ease of maintenance

Built-in hour meter

Triplex Belt Drive General Pump

FEATURES

- Gun/wand assembly with insulated grip and quick connects
- 50'x3/8" high pressure hose w/quick connects
- 20% chemical injector assembly w/quick connects
- 4 colour-coded QC spray nozzles
- 1 colour-coded QC detergent nozzle

WARRANTY

- 3 Year Coil
- 3 Year Honda Engine
- 5 Year Pump

POWERED by **HONDA**



BELT DRIVE

MODEL	GPM	AMPS	PSI	ENGINE	BURNER	BTU/HR	PUMP MODEL	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW3024HG12V	8	17	3000	HONDA GX690	12V-Oil	375,000	GENERAL PUMP TSF2021	2.66 GPH	46"x44"x45"	48"x46"x47"	1079
HW3524HG12V	5.6	17	3500	HONDA GX690	12V-Oil	375,000	GENERAL PUMP TS2021	2.66 GPH	46"x44"x45"	48"x46"x47"	1079