



LED DUAL MODE TUBES

Tunable CCT



PRODUCT FEATURES

- **TUNABLE CCT (3000K/3500K/4000K/5000K/6500K)**
- Direct Replacement / Plug & Play Mode (Type A) *
- Retrofit / Bypass Mode - Double and Single Ended (Type B)
- Film Coated Shatter Resistant Glass Tube
- Instant On / No Flicker
- Continuous Dimming to 10% or below
- IP20 Rated
- 120-277 Voltage Rating, PF > 0.9
- 80+ CRI
- G13 Mounting
- ETL Certified
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature: -4°F to 113°F (-20°C to 45°C)

* See Ballast Compatibility Chart

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLT94-15WAB-T65 5C	L15T8TCABCL94	15	1935	3000	47.78	129	>140°
				3500			
				4000			
				5000			
				6500			
CLT94-18WAB-T65 5C	L18T8TCABCL94	18	2322	3000	47.78	129	>140°
				3500			
				4000			
				5000			
				6500			

