

CAESAR USA RUN

GLAZED PORCELAIN



tierra sol



Nominal Sizes



24x24 -
Rectified



12x24 -
Rectified



6x24 -
Rectified




Colors




Salt



Sunray




Clay



Road

Decors and Special Pieces

2x2 Mosaic



12x12 Sheet



3x24 Bullnose

Special Order:
6x12 Covebase

Recommended applications



Residential



Light commercial



Medium commercial



Bath / Shower



Fireplace



Indoor



Wall



Floor

Characteristics of tile



Low maintenance



Stain resistant



Fade resistant



Hypoallergenic



Resistant to fungus



Odour resistant

Technical specifications



CGSB Type

7



PEI

n/a



Dynamic Coefficient of
Friction

> 0.42



Friction Coefficient

n/a



Frost Resistance

Yes



Water Absorption

< 0.5%



MOHS

6



Tile thickness

9 mm



Chemical
Resistance

Unaffected



Variation

V1

V2

V3

V4

Slight

Special instructions

■ Shade variations between tiles is characteristic. Color may vary from sample.

■ For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.



www.TierraSol.ca