







Ultraviolet Water Purifier Comparison Chart FEATURES [S] - Standard • [O] - Optional • [X] - Yes	 Bio-Logic® Pure Water Pack™ 1.5 GPM ★★★★★ ASSEMBLED IN USA	 MINIPURE® 1 to 9 GPM ★★★★★ ASSEMBLED IN USA	 Ultimate® 4 to 9 GPM ★★★★★ ASSEMBLED IN USA	 MIGHTY★PURE® 3 to 20 GPM ★★★★★ MADE IN THE USA	 SANITRON® 3 to 416 GPM ★★★★★ MADE IN THE USA	 MEGATRON® 90 to 450 GPM ★★★★★ MADE IN THE USA
Chamber Material (Stainless Steel Type)	316	304	304	316	316	316
STER-L-RAY® Germicidal Ultraviolet Lamp with 10,000 Hours Rated Effective Life	S	S	S	S	S	S
Quick Lamp Change with EASY-OFF™ End Cap	S	S	-	S	S	S
CRYSTAL CLEAR™ Quartz Sleeve	S	S	S	S	S	S
Lamp Out Indicator Light(s)	S	S	-	-	-	S
Sight Port to View Lamp Operation	-	-	S	S	S	S
Drain Fitting	-	-	-	S	S	S
Dual Action Wiper Mechanism	-	-	-	-	Manual	Manual or Automatic
Suggested Mount Installation	Horizontal	Horizontal	Vertical	Horizontal	Horizontal	Horizontal
Removable or Rotatable Heads	S	-	-	-	S	S
Alternate Inlet/Outlet Fittings	-	-	-	-	O	O
Sediment and Carbon Filter	S	-	-	-	-	-
Promate™ Mounting Kit / Bracket	S	S	S	O	O ①	-
GUARDIAN™ Ultraviolet Monitor	-	-	-	O	O	S
SENTRY™ Safety Sensor	O	O	-	O	O	-
Promate™ Audio Alarm	S	S	S	O	O	-
Promate™ Solenoid Valve	-	O	-	O	O	-
SureFLO™ Flow Control Valve	-	O	S	O	O	-
Promate™ Elapsed Time Indicator	O	O	-	O	O	S
Promate™ Time Delay Mechanism	-	O	-	O	O	-
Residential Use	X	X	X	X	X	-
Commercial Use	-	-	-	X	X	X
Industrial Use	-	-	-	-	X	X
CE Certified Models ②	-	-	-	X	X	-
NSF Certified Models	-	-	-	X ③	X ④	-

① **SANITRON®** Model S10,000C through S25,000C come equipped with mounting rack.

② **MIGHTY★PURE®** MP36C and **SANITRON®** S37C, S2400C, S5000C, S10,000C, S15,000C, S20,000C, and S25,000C are available as **CE** Certified.

③ **MIGHTY★PURE®** MP36C and MP49C are available with NSF®/ANSI 55 for Disinfection Performance, Class B.

④ **SANITRON®** Models S37C, S50C, and S2400C are certified to NSF®/ANSI 61 & 372. Model S2400C is used in modular form to build larger models.

• When used as directed to disinfect clear water, Atlantic Ultraviolet Corporation® water purifiers provide an ultraviolet dosage in excess of 30,000 micro-watt seconds per square centimeter (µWSec/cm2).

• This list depicts options for 120v 50/60Hz operation. Consult factory for options with other power requirements.



375 Marcus Boulevard
Hauppauge, NY 11788
631.273.0500 • Fax: 631.273.0771
E-mail: info@ultraviolet.com
Ultraviolet.com • BuyUltraviolet.com