

PSA1116



20GA Fine Wire Stapler

Applications

Insulation Installation, Picture Framing, Poly Sheeting, Roofing Felt Installation, Screening, Upholstery

Specifications

Fastener Crown	3/8"
Fastener Length	1/4" - 9/16"
Magazine Capacity	100
Actuation Mode	Dual Trigger Actuation
Dimensions	8" x 2" x 6"
Weight	2.3 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.007 SCF
Noise Power Emissions per EN12549 LwA,1s	91.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	82.0 dBA
Vibration Value	Less than 2.5 m/s ² per ISO-8662-11
Vibration Value Uncertainty per ISO-8662-11	0.70 m/s ²

Features

Bottom Load Steel Magazine, Ergonomic Rubber Grip, Fastener Supply Window, Front Exhaust

Includes

Allen Wrenches, Tool Case, Tool Oil



For Best Results Use Spotnails® Collated Fasteners

20GA 3/8" Crown Fine Wire Staples
(Similar to Rapid® A11 / Arrow® T50)

Stock No.	LENGTH	M/Bx	Bx/Cs
Galvanized, Chisel Point			
85504	1/4"	5.0	20
85505	5/16"	5.0	20
85506	3/8"	5.0	20
85508	1/2"	5.0	20
85509	9/16"	5.0	20
86506	3/8" DP	5.0	20

Retail Packaging

85126	3/8"	1.25	32
-------	------	------	----

304 Stainless Steel

85506SS	3/8"	5.0	20
---------	------	-----	----