

## 1. Identification

### 1.1. Product identifier

**Product Identity** GEORGIA STEEL FRESH GEAR DISINFECTANT (Product Code: FG350-G, GC)

**Alternate Names** GEORGIA STEEL FRESH GEAR DISINFECTANT (Product Code: FG350-G, GC)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** Concentrated hard surface disinfectant cleaner for industrial safety equipment.

### 1.3. Details of the supplier of the safety data sheet

**Company Name** Georgia Steel & Chemical Co., Inc.  
9515 Gerwig Lane, Suite 111  
Columbia, MD 21046

**Emergency** 800-296-0351  
National Poison Center: 800-222-1222

**Customer Service: Georgia Steel & Chemical Co., Inc.** +1(301) 317-5502

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Acute Tox. 5;H303	May be harmful if swallowed. (Note: this GHS classification was not adopted by US OSHA).
Skin Corr. 1B;H314	Causes severe skin burns and eye damage.
Aquatic Acute 1;H400	Very toxic to aquatic life.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

### 2.2. Label elements



**Danger**

H303 May be harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.



Safety Data Sheet  
GEORGIA STEEL FRESH GEAR  
DISINFECTANT (Product Code:  
FG350-G, GC)

SDS Revision  
Date: 12/06/2019

**[Prevention]:**

- P260 Do not breathe dust, fume, mist, vapors or spray.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves, eye protection, face protection.

**[Response]:**

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.
- P303+361+353 IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.
- P304+312 IF INHALED: Call a poison center or doctor or physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.

**[Storage]:**

- P405 Store locked up.

**[Disposal]:**

- P501 Dispose of contents or container in accordance with local and national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1-Decanaminium, N-decyl-N,N-dimethyl-, chloride CAS Number: 0007173-51-5	10 - 25	Acute Tox. 4;H302 Skin Corr. 1B;H314	[1]
Alkylbenzyltrimethylammonium chloride CAS Number: 0068391-01-5	5 - 10	Acute Tox. 4;H302 Skin Corr. 1B;H314 Aquatic Acute 1;H400	[1]
Tetrasodium EDTA CAS Number: 0000064-02-8	1 - 5	Acute Tox. 4;H302 Eye Dam. 1;H318	[1]
1-Octanamine, N,N-dimethyl-, N-oxide CAS Number: 0002605-78-9	1 - 5	Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335	[1]
Ethanol CAS Number: 0000064-17-5	1 - 5	Flam. Liq. 2;H225	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.



**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
Date: 12/06/2019

## Section 4. First aid measures

### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Overview</b>	Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.  Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.
<b>Skin</b>	Causes severe skin burns and eye damage.
<b>Ingestion</b>	May be harmful if swallowed.

## Section 5. Fire-fighting measures

### 5.1. Extinguishing media

Suitable Extinguishing Media: Not applicable. Product is not a fire hazard.

Unsuitable Extinguishing Media: High pressure water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Do not breathe dust, fume, mist, vapors or spray.

### 5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Fire fighters should wear appropriate protective equipment, including self-contained breathing apparatus and impervious clothing.



Safety Data Sheet  
GEORGIA STEEL FRESH GEAR  
DISINFECTANT (Product Code:  
FG350-G, GC)

SDS Revision  
Date: 12/06/2019

ERG Guide No. 154

## Section 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Small spills may be wiped up and rinsed with water. For larger spills, contain spill with inert material (sand, clay). Transfer material to labeled containers for recovery or proper disposal. After removal, flush area with water. Follow good industrial hygiene practices.

## Section 7. Handling and storage

### 7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Read label before use. Avoid contact with skin or eyes. Wash hands, face and any skin contact thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, eye protection, face protection. Use only according to label directions. If unsure about safe use, contact your supervisor.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Do not contaminate water, food or feed by storage and disposal. Store in tightly closed, original container in a cool (10° - 30°C), dry area.

Incompatible materials: No data available.

Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.



Safety Data Sheet  
GEORGIA STEEL FRESH GEAR  
DISINFECTANT (Product Code:  
FG350-G, GC)

SDS Revision  
Date: 12/06/2019

**Section 8. Exposure controls / personal protection**

**8.1. Control parameters**

CAS No.	Ingredient	Exposure	
		Source	Value
0000064-02-8	Tetrasodium EDTA	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0000064-17-5	Ethanol	OSHA	TWA 1000 ppm (1900 mg/m3)
		ACGIH	No Established Limit
		NIOSH	TWA 1000 ppm (1900 mg/m3)
0002605-78-9	1-Octanamine, N,N-dimethyl-, N-oxide	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0007173-51-5	1-Decanaminium, N-decyl-N,N-dimethyl-, chloride	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
0068391-01-5	Alkylbenzyltrimethylammonium chloride	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

**8.2. Exposure controls**

- Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
- Eyes** Protective safety glasses recommended
- Skin** Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Check section 2.2 (GHS Label Elements) for further details.

**Section 9. Physical and chemical properties**

**Appearance**  
**Odor**

Blue Liquid  
Citrus



**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
Date: 12/06/2019

<b>Odor threshold</b>	Not determined
<b>pH</b>	(Conc) - 6.0 - 8.0 (RTU) – 6.0 - 8.0
<b>Melting point / freezing point</b>	Freezing Point : 32°F
<b>Initial boiling point and boiling range</b>	212°F
<b>Flash Point</b>	> 200°F (ASTM D3278)
<b>Evaporation rate (Ether = 1)</b>	Similar to water
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	Not Measured
<b>Relative Density</b>	Not Measured
<b>Solubility in Water</b>	Complete
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Slightly viscous
<b>VOC Content</b>	- 1.1 (Excluding exempt material)
<b>Relative Density</b>	1.005 %
<b>9.2. Other information</b>	
No other relevant information.	

## Section 10. Stability and reactivity

### 10.1. Reactivity

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Temperatures above 50°C or below 10°C.

### 10.5. Incompatible materials

No data available.

### 10.6. Hazardous decomposition products

No hazardous decomposition data available.



**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
 Date: 12/06/2019

**Section 11. Toxicological information**

**Acute toxicity**

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1-Decanaminium, N-decyl-N,N-dimethyl-, chloride - (7173-51-5)	No data available	No data available	No data available	No data available	No data available
Alkylbenzylidimethylammonium chloride - (68391-01-5)	850.00, Rat - Category: 4	2,300.00, Rat - Category: 5	No data available	No data available	No data available
Tetrasodium EDTA - (64-02-8)	1,913.00, Rat - Category: 4	No data available	No data available	No data available	No data available
1-Octanamine, N,N-dimethyl-, N-oxide - (2605-78-9)	No data available	No data available	No data available	No data available	No data available
Ethanol - (64-17-5)	10,470.00, Rat - Category: NA	17,100.00, Rabbit - Category: NA	124.70, Rat - Category: NA	No data available	No data available

**Carcinogen Data**

CAS No.	Ingredient	Source	Value
0000064-02-8	Tetrasodium EDTA	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0000064-17-5	Ethanol	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A3
0002605-78-9	1-Octanamine, N,N-dimethyl-, N-oxide	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit



**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
Date: 12/06/2019

0007173-51-5	1-Decanaminium, N-decyl-N,N-dimethyl-, chloride	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0068391-01-5	Alkylbenzyltrimethylammonium chloride	OSHA	Regulated Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	5	May be harmful if swallowed. (Note: this GHS classification was not adopted by US OSHA).
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

**Section 12. Ecological information**

**12.1. Toxicity**

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
1-Decanaminium, N-decyl-N,N-dimethyl-, chloride - (7173-51-5)	Not Available	Not Available	Not Available
Alkylbenzyltrimethylammonium chloride - (68391-01-5)	0.52, Fish (Piscis)	Not Available	0.80 (96 hr), Algae
Tetrasodium EDTA - (64-02-8)	41.00, Lepomis macrochirus	140.00, Daphnia magna	101.00 (72 hr), Pseudokirchneriella subcapitata





**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
 Date: 12/06/2019

1-Octanamine, N,N-dimethyl-, N-oxide - (2605-78-9)	Not Available	Not Available	Not Available
Ethanol - (64-17-5)	15,400.00, Lepomis macrochirus	> 10,000, Daphnia magna	17.921 (96 hr), Ulva pertusa

**12.2. Persistence and degradability**

There is no data available on the preparation itself.

**12.3. Bioaccumulative potential**

Not Measured

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

This product contains no PBT/vPvB chemicals.

**12.6. Other adverse effects**

No data available.

**Section 13. Disposal considerations**

**13.1. Waste treatment methods**

Observe all federal, state and local regulations when disposing of this substance.

**Section 14. Transport information**

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	UN1903	UN1903	UN1903
<b>14.2. UN proper shipping name</b>	UN1903, Disinfectants, liquid, corrosive n.o.s., (Quaternary ammonium chlorides)), 8, III	Disinfectants, liquid, corrosive n.o.s., (Quaternary ammonium chlorides))	Disinfectants, liquid, corrosive n.o.s., (Quaternary ammonium chlorides))
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class: 8</b>	<b>IMDG: 8</b> <b>Sub Class: Not Applicable</b>	<b>Air Class: 8</b>
<b>14.4. Packing group</b>	III	III	III
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: Yes; ( 1-Decanaminium, N-decyl-N,N-dimethyl-, chloride )		
<b>14.6. Special precautions for user</b>	Not Applicable		



Safety Data Sheet  
GEORGIA STEEL FRESH GEAR  
DISINFECTANT (Product Code:  
FG350-G, GC)

SDS Revision  
Date: 12/06/2019

## Section 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act (TSCA)** All components of this material are either listed or exempt from listing on the TSCA Inventory.

**US EPA Tier II Hazards**

**Fire:** No  
**Sudden Release of Pressure:** No  
**Reactive:** No  
**Immediate (Acute):** Yes  
**Delayed (Chronic):** No

**Note:** Ethanol (Ethyl alcohol) has been placed on the California Proposition 65 Cancer and Developmental Lists when in alcoholic beverages.

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

Ethanol

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 Label Warning:**

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## Section 16. Other information

**SDS Revision Date** 12/06/2019

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.



**Safety Data Sheet**  
**GEORGIA STEEL FRESH GEAR**  
**DISINFECTANT (Product Code:**  
**FG350-G, GC)**

SDS Revision  
Date: 12/06/2019

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document