








Technical features for Dry-Pressed ceramic tiles with water absorption BIII (Eb >10%) Características técnicas para las baldosas cerámicas prensadas en seco del grupo BIII (Eb >10%)		
FEATURES / CARACTERÍSTICAS	SPECIFICATION / ESPECIFICACIÓN	NORMA
 Dimensional Features	74.0 +/- 0.6 x 149.5 +/-0.6 x 10 +/-0.6 mm 74.0 +/- 0.6 x 300.0 +/- 0.6 x 10 +/-0.6 mm 48.0 +/- 0.6 x 248. +/-0.6 x 10 +/-0.6 mm 48.0 +/- 0.6 x 500. +/-0.6 x 10 +/-0.6 mm	UNE-EN ISO 10545-2:1998
 Water absorption	$E_b > 10\%$	UNE-EN ISO 10545-3:1997
 Modulus of rupture and breaking strength	Thinkness $\leq 7,5$ mm mínimo 15 N/mm ² Thinkness $> 7,5$ mm mínimo 12 N/mm ²	UNE-EN ISO 10545-4:2012
 Crazing resistance	Pass	UNE-EN ISO 10545-11:1997
 Household products resistance.	GA	UNE-EN ISO 10545-13:1998
 Chemical resistance	GLA	UNE-EN ISO 10545-13:1998
 Stain resistance	Class 5	UNE-EN ISO 10545-14:1998