

ANGORA SEGMENT



DOUBLE LOADED UNGLAZED RECTIFIED PORCELAIN, FULL COMMERCIAL & RESIDENTIAL

Angora Segment is a double loaded unglazed rectified residential and commercial porcelain tile series. The wide range of colours and options work perfectly in contemporary and a variety of other settings.



Nominal Sizes



12x24 Natural




12x24 Polished



50/50


Colours




Ice




Ivory




Smoke




Clay



Mocha



Carbon



Charcoal

Special Order with an approximate 30 day delivery. Deposit required. Prices on request only from your sales representative.
12x12 Natural, 24x24 Natural, 12x12 Polished, 24x24 Polished

Recommended applications



Residential



Light commercial



Medium commercial



Bath / Shower



Fireplace



Heavy commercial



Wall



Floor



Indoor

Characteristics of tile



Low maintenance



Stain resistant



Fade resistant



Hypoallergenic



Resistant to fungus



Odour resistant

Technical specifications



CGSB Type

7



PEI

n/a



Dynamic Coefficient of Friction

≥ 0.42



Friction Coefficient

Dry: 0.9
Wet: 0.7



Frost Resistance

Yes



Water Absorption

≤ 0.5%



MOHS

7



Tile thickness

10 mm



Chemical Resistance

Class A



Variation

Uniform
V1 V2 V3 V4

Special instructions

- Sealing the polished tiles is recommended prior to grouting. This is basically done as a grout release. Wipe on, wait 5 minutes, and then wipe off 100%. No sealer residue can be left on the surface prior to grouting.
- Shade variations between tiles is characteristic. Colour may vary from sample.
- For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.



50/50



www.TierraSol.ca