



# McKINLEY LVT

2.5MM x 12" x 24" | 22MIL



## TECHNICAL DATA SHEET

<b>USAGE AREAS</b>	<b>RESIDENTIAL/COMMERCIAL BUILDINGS, RETAIL, HEALTHCARE, HOSPITALITY, EDUCATION</b>
--------------------	---

Size	CTN PACKAGING	CONTAINER PACKAGING
7" x 48"	18 PCS/CTN 43.5 SF/CTN	50 CTN/PLT 2175 SF/PLT
12" x 24"	22 PCS/CTN 44 SF/CTN	48 CTN/PLT 2112.02 SF/PLT

CERTIFICATION & CLASSIFICATION	STANDARD	MCKINLEY RESULTS
TYPE OF FLOOR COVERING	ASTM F1700	HETEROGENEOUS FLOOR COVERING   LUXURY VINYL TILE
CLASSIFICATION	ASTM F1700	CLASS III/ TYPE B
CE CERTIFICATION/ FLOORSORE	EN 14041	YES

TECHNICAL PERFORMANCE	STANDARD	MCKINLEY RESULTS
DIMENSIONAL STABILITY	ASTM F2199	PASSES, ≤0.10%
RESIDUAL INDENTATION	ASTM F1914	PASSES, ≤ 5%
FLEXIBILITY	ASTM F137	NO CRACK OR BREAK
COLOR FASTNESS TO HEAT	ASTM F1514	PASSES
COLOR FASTNESS TO LIGHT	ASTM F1515	PASSES
STAINING & RESISTANCE TO CHEMICALS	ASTM F925	PASSES
SLIP RESISTANCE	DIN 51130   EN 13893	R 10   CLASS DS
REACTION TO FIRE	EN 13501 - 1	CLASS BFL-S1
WEAR RESISTANCE	EN 660-1	GROUP T
CASTOR CHAIR	EN ISO 4918 (EN 425)	NO DAMAGE

TECHNICAL CHARACTERISTICS	STANDARD	MCKINLEY RESULTS
TOTAL THICKNESS	ASTM F386	2.5 MM, PASSES
WEAR LAYER THICKNESS	ASTM F410	0.55 MM   22 MIL, PASSES
SIZE	ASTM F2055	2.5mm x 7" x 48", PASSES 2.5mm x 12" x 24", PASSES
SURFACE TREATMENT	UV TREATED	PUR   RQ PROTECT
RECYCLED MATERIAL CONTENT		NO POST-CONSUMER WASTE