



844-pik-fast • www.pik-fast.com

PRODUCT DATA SHEET

FM670F - Fillet Tape

Description:

A double-sided ultra-bond tape designed to adhere to the backside of a mat, wood, or metal fillets. Our acrylic adhesive will not yellow or dry out. Rough surfaces will not cause any problems when bonding and usage of this tape will reduce shrinkage and elongation with its extreme holding power.

Features:

- Clear tape on white paper liner
- Suitable for outdoor use
 - Withstands temperature variations
 - Water and moisture resistant
- Good UV resistance

Ⓜ FM670F-.25 1/4" x 36YD



Product Data				
Carrier	Polypropylene	1.2 mil	0.03 mm	
Adhesive (each side)	Acrylic	3.5 mil	0.09 mm	
Liner	White glassine paper	3.0 mil	0.08 mm	
Total Tape Thickness	-	11.2 mil	0.29 mm	
Peel Adhesion	From Stainless Steel	80 oz/in	22 N/25 mm	
Temperature Resistance	-	200°F	93°C	
Recommended Industry	Framing	Awards	Signs	Trophies

Application Notes:

Aggressive and durable adhesive makes it a great all-around tape that can be used in many applications that require a double-sided tape. Also used in custom ribbon bow making.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity