



Equipped with a keyed or rotary switch, this unit allows quick control of your HVAC systems like fans, dampers, and more.

## SPECIFICATIONS

Compatible with all IAM and IAV units. Every ICMHOA has a black background with white screened legend and LED point illumination in green and yellow. Controls any HVAC units requiring 24 VDC or dry contact interface. LEDs only light after “positive feedback” is received from the field onto TB2 in the form of a closed contact. If an ICMLEDTST is installed, all of the LEDs should light when the switch is activated, regardless of the state of an ICMENGAGE, if installed. If an ICMLEDTST and an ICMENGAGE are part of the control line, the ICMENGAGE must be wired electrically after the ICMLEDTST. Standard clinch type terminal strip used for field wiring.

## FEATURES

- Legend sheet protected by scratch-resistant Lexan® viewing window
- Durable steel frame mounts into an Infinity Gang Box or standard electrical back box and securely holds the Infinity Gang Plate
- Standard legend slip sheet and all mounting hardware included



## RATINGS AND RESISTIVE LOAD

**Rotary:** 1 Amp @24VDC/VAC **Keyed:** 3 Amps @24VDC/VAC

## CURRENT REQUIREMENT

8mA “On” and 8mA “Off” @24VDC/VAC

## AGENCY APPROVALS

- UOXX.S2580 UL Listed Control Unit Accessories
- UUKL.S2580 UL Listed Smoke-control System Equipment
- 7120-0553:0105 California State Fire Marshal (CSFM)

## ORDERING INFORMATION

Part #	Description
ICMHOAK (SSU02526)	Smoke Control (Keyed)
ICMHOAR (SSU02525)	Smoke Control (Rotary)